



NEXUS

90cm & 110cm Available in Dual Fuel & Induction



Telescopic shelves



*Bread proving drawer
110cm models*



*Bridging zone with griddle plate
Induction hobs only*

Choose your colour



MADE IN BRITAIN
SINCE 1830

Specifications - Nexus

	NEXUS 90 DUAL FUEL	NEXUS 90 INDUCTION	NEXUS 110 DUAL FUEL	NEXUS 110 INDUCTION
MODEL NUMBER	NEX90DF + COLOUR	NEX90EI + COLOUR	NEX110DF + COLOUR	NEX110EI + COLOUR
WIDTH (MM)	900	900	1092	1100
DEPTH EX INC HANDLES (MM)	608 648	608 648	608 648	608 648
HEIGHT - UP TO HOTPLATE (MM)	905-930 [^]	905-930 [^]	905-930 [^]	905-930 [^]
HOB RATINGS - KW ELECTRIC, MJ GAS	1 X 3.8 - 15.2MJ 1 X 3.0 - 12.3MJ 2 X 1.55 - 6.2MJ 1 X 0.82 - 3.7MJ	3 X 1.85 - 2.50KW 1 X 1.85 - 3.20KW 1 X 1.15 - 2.00KW -	1 X 3.8 - 15.2MJ 1 X 3.0 - 12.3MJ 2 X 1.55 - 6.2MJ 1 X 0.82 - 3.7MJ	3 X 1.85 - 2.50KW 1 X 1.85 - 3.20KW 1 X 1.15 - 2.00KW -
BRIDGING ZONE	NO	1.85KW	NO	1.85KW
CERAMIC BURNER (MULTI ZONE) WITH GRIDDLE	NO	NO	2 X 1.10KW	NO
TOTAL MJ RATING **	43.6	N/A	43.6	N/A
RATED CONNECTED LOAD (KW) @230V	7.4	14	10	15.5
RATED CONNECTED LOAD (AMPS) @230V	33	65	44	68
ELECTRICAL CONNECTION (AMPS) #	N/A	#40	#40	#40
THREE-PHASE CONNECTION (AMPS). CONSULT WITH A LICENSED ELECTRICIAN.	3 X 16A	3 X 25A	3 X 16A	3 X 25A
OVEN CAPACITY LITRES LH RH >	79 67	79 67	79 79	79 79
OVEN TEMPERATURE	80°C - 240°C	80°C - 240°C	80°C - 240°C	80°C - 240°C
TELESCOPIC SHELVES SUITS BOTH OR LH OVEN	INCLUDED LH	INCLUDED LH	INCLUDED BOTH	INCLUDED BOTH
OVEN FUEL LH RH	ELECTRIC ELECTRIC	ELECTRIC ELECTRIC	ELECTRIC ELECTRIC	ELECTRIC ELECTRIC
OVEN TYPE LH RH	MULTIFUNCTION FAN	MULTIFUNCTION FAN	MULTIFUNCTION FAN	MULTIFUNCTION FAN
INTERNAL OVEN CAVITY WXD XH (MM) - LEFT	466 X 385 X 438	466 X 385 X 438	466 X 385 X 438	466 X 385 X 438
INTERNAL OVEN CAVITY WXD XH (MM) - RIGHT	296 X 386 X 575	296 X 386 X 575	466 X 385 X 438	466 X 385 X 438
SEPARATE GRILL	DELUXE GLIDE OUT	DELUXE GLIDE OUT	DELUXE GLIDE OUT	DELUXE GLIDE OUT
GRILL FUEL	ELECTRIC	ELECTRIC	ELECTRIC	ELECTRIC
GRIDDLE	SUPPLIED SIT-ON, OPTIONAL TEPPANYAKI	N/A	SUPPLIED MULTI-ZONE FOR CERAMIC BURNERS, OPTIONAL TEPPANYAKI & SIT-ON GRIDDLE	SUPPLIED INDUCTION GRIDDLE
WOK CRADLE	SUPPLIED	N/A	SUPPLIED	N/A
CAST IRON PAN SUPPORTS	YES	N/A	YES	N/A
FLAME FAILURE SAFETY DEVICE	YES	N/A	YES	N/A
ELECTRONIC IGNITION	UNDER KNOB	N/A	UNDER KNOB	N/A
PAN DETECTOR	N/A	YES	N/A	YES
RESIDUAL HEAT INDICATORS	N/A	YES	N/A	YES
LOW TEMPERATURE SETTINGS (HOB)	N/A	3	N/A	3
CHILD LOCK (HOB CTRLS)	N/A	YES	N/A	YES
PROGRAMMABLE CLOCK & CHILD LOCK (OVEN CTRLS)	YES (LEFT HAND OVEN)	YES (LEFT HAND OVEN)	YES (LEFT HAND OVEN)	YES (LEFT HAND OVEN)
MINUTE MINDER	YES	YES	YES	YES
DOOR OPENING LH RH	SIDE SIDE	SIDE SIDE	SIDE SIDE	SIDE SIDE
DOOR TYPE LH RH	PORTHOLE SOLID	PORTHOLE SOLID	PORTHOLE PORTHOLE	PORTHOLE PORTHOLE
OVEN LIGHT	X1	X1	X2	X2
CATALYTIC LINERS	SIDES (LH)	SIDES (LH)	SIDES	SIDES
BREAD PROVING & STORAGE DRAWER	NO	NO	YES	YES
DOOR GLAZING	TRIPLE	TRIPLE	TRIPLE	TRIPLE
OVEN FUNCTIONS				
BASE HEAT	YES	YES	YES	YES
BROWNING ELEMENT	YES	YES	YES	YES
CONVENTIONAL OVEN	YES	YES	YES	YES
DEFROST	YES	YES	YES	YES
FAN ASSISTED	YES	YES	YES	YES
FANNED GRILLING	YES	YES	YES	YES
FAN OVEN	YES	YES	YES	YES
AVAILABLE COLOURS				
BLACK	YES	YES	YES	YES
WHITE	YES	YES	YES	YES
STAINLESS STEEL	YES	YES	YES	YES
SLATE	YES	YES	YES	YES
FITTINGS	SATIN CHROME	SATIN CHROME	SATIN CHROME	SATIN CHROME
WEIGHT	113KG	111KG	135KG	131KG
5 YEAR WARRANTY	YES	YES	YES	YES



110cm Induction



110cm Gas



90cm Gas



90cm Induction



KEY: [^] Adjustable height, LH Left hand oven, RH Right hand oven, ** Incl. oven where applicable, « Multi ring wok burner, > Litres based on European Standards | Measurements, #Using assessed maximum demand. Not all zones can be used at once. Consult with a licensed electrician.