




NEXUS SE


110cm Available in Dual Fuel & Induction



Slow oven



*Bridging zone with griddle plate
Induction hobs only*



Telescopic shelves

Choose your colour



 **MADE IN
BRITAIN**
SINCE 1830

Specifications - Nexus SE

	NEXUS SE 110 DUAL FUEL	NEXUS SE 110 INDUCTION
MODEL NUMBER	NEXSE110DF + COLOUR	NEXSE110EI + COLOUR
WIDTH (MM)	1092	1100
DEPTH EX INC HANDLES (MM)	608 648	608 646
HEIGHT - UP TO HOTPLATE (MM)	905-930^	905-930^
HOB RATINGS - KW ELECTRIC, MJ GAS	1 X 3.8 - 15.2MJ 1 X 3.0 - 12.3MJ 2 X 1.55 - 6.2MJ 1 X 0.82 - 3.7MJ	3 X 1.85 - 2.50KW 1 X 1.85 - 3.20KW 1 X 1.15 - 2.00KW -
BRIDGING ZONE	NO	1.85KW
CERAMIC BURNER (MULTI ZONE) WITH GRIDDLE	2 X 1.10KW	NO
TOTAL MJ RATING **	43.6	N/A
RATED CONNECTED LOAD (KW) @230V	11.8	17
RATED CONNECTED LOAD (AMPS) @230V	52	74
ELECTRICAL CONNECTION (AMPS) #	#40	#40
THREE-PHASE CONNECTION (AMPS). CONSULT WITH A LICENSED ELECTRICIAN.	3 X 20A	3 X 25A
OVEN CAPACITY LITRES LH RH >	79 79	79 79
OVEN TEMPERATURE	80°C - 240°C	80°C - 240°C
SLOW COOK OVEN CAPACITY LITRES RH TOP	21	21
SLOW COOK OVEN TEMPERATURE	80°C - 140°C	80°C - 140°C
TELESCOPIC SHELVES SUITS BOTH OR LH OVEN	INCLUDED BOTH	INCLUDED BOTH
OVEN FUEL LH RH	ELECTRIC ELECTRIC	ELECTRIC ELECTRIC
OVEN TYPE LH RH	MULTIFUNCTION FAN	MULTIFUNCTION FAN
INTERNAL OVEN CAVITY WXD XH (MM) - LEFT	466 X 385 X 438	466 X 385 X 438
INTERNAL OVEN CAVITY WXD XH (MM) - RIGHT	466 X 385 X 438	466 X 385 X 438
SEPARATE GRILL	DELUXE GLIDE OUT	DELUXE GLIDE OUT
GRILL FUEL	ELECTRIC	ELECTRIC
GRIDDLE	SUPPLIED MULTI-ZONE FOR CERAMIC BURNERS, OPTIONAL TEPPANYAKI & SIT-ON GRIDDLE	SUPPLIED INDUCTION GRIDDLE
WOK CRADLE	SUPPLIED	N/A
CAST IRON PAN SUPPORTS	YES	N/A
FLAME FAILURE SAFETY DEVICE	YES	N/A
ELECTRONIC IGNITION	UNDER KNOB	N/A
PAN DETECTOR	N/A	YES
RESIDUAL HEAT INDICATORS	N/A	YES
LOW TEMPERATURE SETTINGS (HOB)	N/A	3
CHILD LOCK (HOB CTRLS)	N/A	YES
PROGRAMMABLE CLOCK & CHILD LOCK (OVEN CTRLS)	YES (LEFT HAND OVEN)	YES (LEFT HAND OVEN)
MINUTE MINDER	YES	YES
DOOR OPENING LH RH	SIDE SIDE	SIDE SIDE
DOOR TYPE LH RH	PORTHOLE PORTHOLE	PORTHOLE PORTHOLE
OVEN LIGHT	X2	X2
CATALYTIC LINERS	SIDES	SIDES
DOOR GLAZING	TRIPLE	TRIPLE
OVEN FUNCTIONS		
BASE HEAT	YES	YES
BROWNING ELEMENT	YES	YES
CONVENTIONAL OVEN	YES	YES
DEFROST	YES	YES
FAN ASSISTED	YES	YES
FANNED GRILLING	YES	YES
FAN OVEN	YES	YES
RAPID RESPONSE	YES	YES
AVAILABLE COLOURS		
BLACK	YES	YES
STAINLESS STEEL	YES	YES
SLATE	YES	YES
IVORY	YES	YES
FITTINGS	SATIN CHROME	SATIN CHROME
WEIGHT	145KG	145KG
5 YEAR WARRANTY	YES	YES



110cm Gas



110cm Induction



KEY: ^ Adjustable height, LH Left hand oven, RH Right hand oven, ** Incl. oven where applicable, « Multi ring wok burner, > Litres based on European Standards | Measurements, #Using assessed maximum demand. Not all zones can be used at once. Consult with a licensed electrician.