

## WCD120 WCS 8kg

W1 Front-loading washing machine with 1–8 kg honeycomb drum and Pre-ironing for gently cared-for laundry



- Gentle laundry care thanks to the Miele honeycomb drum
- Ironing made easy thanks to preironing
- Perfect supplement for specific applications CapDosing
- Easy fingertip operation DirectSensor
- Cost-efficient, powerful & no wear and tear the ProfiEco Motor

Price \$ 1,699.00\*\*

\*\* GST inclusive

Pre-ironing for gently cared-for laundry	/
Construction type	
Suitable for stacking	•
Side-by-side	•
Slot-in	•
Can be built-under	•
Door hinge	right
Model	
Product brand	W1 Chrome Edition
Front-loader	•
Spinning	
Max. spin speed	1,400
Rinse hold	•
"Without spin" function	•
Design	
Appliance colour	Lotus white
Control panel colour	Lotus white
Door design	Lotus white
Rotary selector colour	Lotus White
Control panel version	Straight
Control type	Rotary selector
Display	DirectSensor yellow, 7 segment
Cleaning performance	
CapDosing	•
Gentle laundry care	
Honeycomb drum	<u>•</u>
Load in kg	8.0
User convenience	
Delay start up to 24 hours	<u>•</u>
Time left display	<u>•</u>
AutoClean detergent drawer	•
Efficiency and sustainability	
Low temperature wash "Cold" and "20 °C"	•
Automatic load control	
Foam sensing	•
ProfiEco motor	•



## WCD120 WCS 8kg

W1 Front-loading washing machine

with 1-8 kg honeycomb drum and Pre-ironing for gently cared-for laundry



Wash programmes	
Cottons (coloureds)	<u> </u>
Minimum iron	•
Delicates	•
Shirts	•
Woollens (hand-washable)	•
Express 20	•
Dark garments / Denim	•
Proofing	•
Cottons Eco	•
Separate rinse/Starch	•
Drain / Spin	•
ECO 40-60	•
Extras	
Short	<u> </u>
Pre-wash	•
Water plus	•
Additional rinse cycle	•
Pre-ironing	•
Quality	
Suds container	Stainless Steel
Counterweights made of cast iron	•
Safety	
Water control system	<u>•</u>
PIN code lock	•
Technical data	
Dimensions in mm (width)	596
Dimensions in mm (height)	850
Dimensions in mm (depth)	636
Appliance depth in mm with opened door	1,054.0
Weight in kg	86.00
Total rated load in kW	2.300
Voltage in V	230
Fuse rating in A	10
Length of supply lead in m	2