




ZIP HYDROTAP MINIBOIL B



BOILING

FILTERED



Order Code HT1017Z3

Zip HydroTap Miniboil, Boiling, Filtered water appliance featuring a stylish touch activated tap and a compact under bench command centre with externally mounted water filtration.

Manufacturing Code 2500AU3M2ZN1R

Capacity Residential

Disability Options Unavailable

Tap Zip HydroTap Miniboil CLASSIC Tap (Matte Black)

Water Pressure	Min 172kPa - Max 700kPa
Water Connection	12.7mm BSP
Water Supply Requirements	Cold
Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
Power Rating	1.5kW 220-240V 50/ 60 Hz
Power Supply	1 x 10Amp GPO
Dimensions	H338mm x W212mm x D269mm
Product Approvals	WaterMark, CE, RCM
Warranty	12 months

Installation Requirements

- "1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.
3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.
4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com"

Installation Detail

