


KPFA12T

Decorative wall hood, Portofino, Turquoise, 120 cm



TYPE

Product family: Hood • Hood Type: Decorative wall hood • Hood width: 120 cm • Extraction: Extraction • EAN code: 8017709293529

AESTHETICS

Colour: Turquoise • Aesthetics: Portofino • Design: Chimney • Material: Stainless Steel + Painted Material • Type of steel: Brushed

CONTROLS

Control setting: Control knobs • Control knobs: Portofino • No. of controls: 2 • Controls colour: Steel effect

PROGRAMS / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes

TECHNICAL FEATURES

No. of lights: 4 • Light type: LED • Light Power: 4 W • Light color temperature scale (°K): 4000 °K • Light color temperature range: 3000° - 5700°K °K • Free outlet maximum capacity: 815 m³/h • Motor power: 275 W • No. of filters: 4 • Anti-grease filters: Stainless steel • Minimum distance from GAS hob: 650 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 650 mm • Non return valve: Yes

PERFORMANCE / ENERGY LABEL

Annual Efficiency Consumption (AEChood): 42 kWh/a • Fluid Dynamic Efficiency (FDE): 36.3 • Lighting Efficiency (LE): 74.8 lux/W • Grease Filtering Efficiency (GFE): 74.9 % • Air flow at minimum speed (Qmin): 287 m³/h • Air flow at maximum speed (Qmax): 606 m³/h • Air flow at boost speed (Qboost): 777 m³/h • Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 49 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 67 dB(A) • Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost): 73 dB(A) • Time increase factor (F): 0.7 • Energy Efficiency Index: 41.4 • Measured air flow rate at best efficiency point (Qbep): 400 m³/h • Measured air pressure at best efficiency point (Pbep): 490 Pa • Measured electric power input at best efficiency point (Wbep): 150 W • Nominal Power consumption of the light system (WL): 4 W • Average illumination of the light on the cooking surface (Emiddle): 329 lux • Sound power level at highest setting (Lwa): 67 dB(A)

ELECTRICAL CONNECTION

Voltage: 220-240 V • Frequency (Hz): 50-60 Hz

SPEED 1

Extraction rate IEC 61591: 287 m³/h • Noise level IEC 60704-2-13: 49 dB(A) • Power: 176 W

SPEED 2

Extraction rate IEC 61591: 389 m³/h • Noise level IEC 60704-2-13: 58 dB(A) • Power: 230 W

SPEED 3

Extraction rate IEC 61591: 606 m³/h • Noise level IEC 60704-2-13: 67 dB(A) • Power: 260 W

INTENSIVE SPEED

Extraction rate (IEC 61591): 777 m³/h • Noise level IEC 60704-2-13: 73 dB(A) • Power: 286 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 1227x1196x495 • Width: 1196 mm • Depth (mm): 495 mm • Product Height (mm): 1227 mm

