

## KPF12BL

Decorative wall hood, Portofino, Black, 120 cm



### TYPE

Product family: Hood • Hood Type: Decorative wall hood • Hood width: 120 cm • Extraction: Extraction • EAN code: 8017709261634

### AESTHETICS

Colour: Black • Aesthetics: Portofino • Design: Chimney • Material: Stainless Steel + Painted Material • Type of steel: Brushed

### CONTROLS

Control setting: Control knobs • Control knobs: Portofino • No. of controls: 2 • Controls colour: Steel effect

### PROGRAMS / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes

### TECHNICAL FEATURES

No. of lights: 4 • Light type: LED • Light Power: 4 W • Light color temperature scale (°K): 4000 °K • Free outlet maximum capacity: 815 m<sup>3</sup>/h • Motor power: 275 W • No. of filters: 4 • Anti-grease filters: Stainless steel • Minimum distance from GAS hob: 650 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 650 mm • Non return valve: Yes

## PERFORMANCE / ENERGY LABEL

Fluid Dynamic Efficiency class (FDEC): A • Grease Filtering Efficiency Class (GFEC): D • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC<sub>hood</sub>): 42 kWh/a • Fluid Dynamic Efficiency (FDE): 36.3 • Lighting Efficiency (LE): 74.8 lux/W • Grease Filtering Efficiency (GFE): 74.9 % • Air flow at minimum speed (Q<sub>min</sub>): 287 m<sup>3</sup>/h • Air flow at maximum speed (Q<sub>max</sub>): 606 m<sup>3</sup>/h • Air flow at boost speed (Q<sub>boost</sub>): 777 m<sup>3</sup>/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE<sub>min</sub>): 49 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE<sub>max</sub>): 67 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPE<sub>boost</sub>): 73 dB(A) • Time increase factor (F): 0.7 • Energy Efficiency Index: 41.4 • Measured air flow rate at best efficiency point (Q<sub>bep</sub>): 400 m<sup>3</sup>/h • Measured air pressure at best efficiency point (P<sub>bep</sub>): 490 Pa • Measured electric power input at best efficiency point (W<sub>bep</sub>): 150 W • Nominal Power consumption of the light system (WL): 4 W • Average illumination of the light on the cooking surface (E<sub>middle</sub>): 329 lux • Sound power level at highest setting (L<sub>wa</sub>): 67 dB(A)

## ELECTRICAL CONNECTION

Electrical connection rating: 280 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz

### SPEED 1

Extraction rate IEC 61591: 287 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 49 dB(A) • Power: 176 W

### SPEED 2

Extraction rate IEC 61591: 389 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 58 dB(A) • Power: 230 W

### SPEED 3

Extraction rate IEC 61591: 606 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 67 dB(A) • Power: 260 W

### INTENSIVE SPEED

Extraction rate (IEC 61591): 777 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 73 dB(A) • Power: 286 W

## LOGISTIC INFORMATION

Dimensions of the product (mm): 1227x1196x495 • Width: 1196 mm • Depth (mm): 495 mm • Product Height (mm): 1227 mm

