

Revision: 0

Date: May 2019

Supersedes all previous issues

Elvire Invisi II Cleanflush[™]

4.5/3 litre Dual Flush Toilet Suite with Elvire Cleanflush™ Wall Hung Rimless Vitreous China Pan and Invisi II Cistern for Inwall, Under Counter, Induct or Inceiling applications









Elvire Invisi II Cleanflush

4.5/3 litre Dual Flush Toilet Suite with Elvire Cleanflush™ Vitreous China Wall Hung Rimless Pan and Invisi II Cistern for Inwall, **Under Counter, Induct or Inceiling applications**





Inspired by the unique nature and wilderness of Australia, the Elvire collection evokes a harmony of design, ergonomics and aesthetics. Combining a soft, natural design with rimless pan technology, the Elvire **Cleanflush**[™] is a superior flushing system suitable for domestic and commercial applications. Incorporating several patented technologies: Caroma Flow Splitter[™], Caroma Flow Balancer[™] and Caroma Uni-Orbital[®] Connector, the Cleanflush pan is innovative and the next evolution in toilets. The Flow Splitter evenly flows water around the top of the bowl to meet at the Flow Balancer which directs the water powerfully into the sump, reducing the need for brush cleaning. The rimless pan is easy to clean and unlike traditional pan profiles, provides full visibility of any grime build up. Caroma Cleanflush provides a cleaner clean for peace of mind.

Elvire Cleanflush™ 4.5 litre wall hung full flush rimless pan.

P-trap only unvented. Traps:

Inlet: Fully glazed 50mm back inlet for concealed cistern and flushvalve installation. Invisi II cistern - suitable for inwall, under counter, induct and inceiling applications. Cistern: For push button and access plate (supplied separately) options see 6.15.1.

Fixing: Invisi II Wall Hung Pan Bracket options — D.403 Standard Code No.237403,

D.402 Undercounter Code No.237402

Sanifix Wall Hung Pan Bracket options - D.788 Bolt Through the Wall Bracket

Code No.687788

Note: The bracket systems are suitable for installation only where non compressible

wall materials are used.

Cistern - the cistern and bracket for under counter or inwall Invisi II systems are pre-assembled and are supplied with the flush pipe and a waste pipe suitable for

installation in a 90mm cavity wall. Structural brick wall systems require the cistern to be fixed to the wall. For in wall applications with raised height cisterns an extension kit is provided with the kit.

Seats:

Colours:

Dimensions:

The **Elvire** soft close toilet seat is provided as standard with this suite. A quality solid section compression moulded toilet seat, fitted with buffers and metal hinges.

Installation: The installation of the toilet suite shall be in accordance with the normal minimum

drainline grade requirements in AS/NZS 3500.2.

All dimensions are in millimetres and are subject to normal manufacturing variations.

Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

