


ZIP HYDROTAP MINIBOIL BA CLASSIC TAP CHROME



Order Code MB1716Z00

Zip HydroTap Miniboil, Boiling and Ambient, Filtered water appliance featuring a stylish touch activated tap and a compact under bench command centre with externally mounted water filtration.



Manufacturing Code	MB1716Z00	
Capacity	Residential	

Water PressureMin 170kPa - Max 700kPaWater Connection1/2" BSP (G1/2)Water Supply RequirementsColdWater ValvesIntegrated 500kPa Pressure limiting valve and Dual Check ValvePower Rating1.35kW 220-240V 50HzPower Supply1 x 10 Amp socket outletDimensionsW212mm x D269mm x H338mmProduct ApprovalsWaterMark, RCM		
Water Connection1/2" BSP (G1/2)Water Supply RequirementsColdWater ValvesIntegrated 500kPa Pressure limiting valve and Dual Check ValvePower Rating1.35kW 220-240V 50HzPower Supply1 x 10 Amp socket outletDimensionsW212mm x D269mm x H338mmProduct ApprovalsWaterMark, RCM	Тар	Zip HydroTap Miniboil CLASSIC Tap (Chrome)
Water Supply RequirementsColdWater ValvesIntegrated 500kPa Pressure limiting valve and Dual Check ValvePower Rating1.35kW 220-240V 50HzPower Supply1 x 10 Amp socket outletDimensionsW212mm x D269mm x H338mmProduct ApprovalsWaterMark, RCM	Water Pressure	Min 170kPa - Max 700kPa
RequirementsWater ValvesIntegrated 500kPa Pressure limiting valve and Dual Check ValvePower Rating1.35kW 220-240V 50HzPower Supply1 x 10 Amp socket outletDimensionsW212mm x D269mm x H338mmProduct ApprovalsWaterMark, RCM	Water Connection	1/2" BSP (G1/2)
Power Rating 1.35kW 220-240V 50Hz Power Supply 1 x 10 Amp socket outlet Dimensions W212mm x D269mm x H338mm Product Approvals Water Mark, RCM	Water Supply Requirements	Cold
Power Supply 1 x 10 Amp socket outlet Dimensions W212mm x D269mm x H338mm Product Approvals WaterMark, RCM	Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
Dimensions W212mm x D269mm x H338mm Product Approvals WaterMark, RCM	Power Rating	1.35kW 220-240V 50Hz
Product Approvals WaterMark, RCM	Power Supply	1 x 10 Amp socket outlet
	Dimensions	W212mm x D269mm x H338mm
Warranty 12 months	Product Approvals	WaterMark, RCM
	Warranty	12 months

Installation Requirements

https://www.zipwater.com/shop/hydrotap/zip-hydrotap-miniboil-ba-ht1716Z00/zip-hydrotap-miniboil-ba-ht1716Z00

8/31/2021

Zip HydroTap Miniboil BA Classic Tap Chrome | Zip Water

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com

Installation Detail

