



AC200180

Canopy extractor 200 series
Stainless steel and glass
Width 70 cm
Air extraction/Air recirculation

- Can be integrated invisibly in upper cabinet
- Energy-saving, low-noise fan
- Rim extraction with flat and easy-to-clean glass cover
- Dimmable, warm white LED light for ideal illumination of the whole cooktop
- Air extraction or air recirculation system
- Energy efficiency class A

Output

- Performance and noise level, output level 3/Intensive:
 Air output according to EN 61591.
 Sound power level according to EN 60704-3.
 Sound pressure level according to EN 60704-2-13.
 Odour reduction for air recirculation in accordance with EN 61591.
- Air extraction:
 570 / 770 m³/h.
 65 / 72 dB (A) re 1 pW.
 51 / 58 dB (A) re 20 µPa.
- Air recirculation:
 320 / 370 m³/h.
 73 / 77 dB (A) re 1 pW.
 59 / 63 dB (A) re 20 µPa.

Features

- 3 electronically controlled power levels and 1 intensive mode.
- Remote control is available as a special accessory.
- Interval ventilation, 6 min.
- Run-on function, 6 min.
- Grease filter saturation indicator.
- Metal grease filter, dishwasher-safe.
- Glas filtercover.
- Warm white surface LED light (4000 K), continuously dimmable.
- Lamp output 2 x 1 W.
- Illuminance 244 lx.
- Fan technology with highly efficient, brushless DC motor (BLDC).


Consumption data

- Energy efficiency class A.
- Energy consumption 49.1 kwh/year.
- Ventilation efficiency class A.
- Illumination efficiency class A.
- Grease filter efficiency class D.
- Sound level min. 42 dB / max. 65 dB normal mode.

Planning notes

- Can be integrated invisibly in upper cabinet.
- Suitable for the installation in 80 cm cabinet.
- For ceiling installation with intensive production of vapours like MPA/DA/E should

Included accessories



Optional accessories

- AA200111 Active carbon filter
- AA200510 Remote control
- AA200810 Recirculating kit

Alternative colors available

Technical Data

Characteristics

Typology : Traditional
 Approval certificates : CE, VDE
 Length electrical supply cord (cm) : 100
 Required niche size for installation (HxWxD) : 418mm x 676mm x 264mm
 Net weight (kg) : 9.0
 Type of control : Electronic
 Number of speed settings : 3
 Maximum output air extraction (m3/h) : 570
 Boost position output recirculating (m3/h) : 370
 Maximum output recirculating air (m3/h) : 320
 Boost position air extraction (m3/h) : 770
 Number of lights : 2
 Noise level (dB) : 65
 Diameter of air outlet (mm) : 150 / 120
 Grease filter material : Washable synthetic
 Odour filter : No
 Operating Mode : Convertible
 Delay Shut off modes : 6M
 Optional accessories : AA200111, AA200510, AA200810
 Type of lamps used : LED
 Total power of the lamps (W) : 2
 Grease filter type : Kassette

Consumption and connection features

Connection Rating (W) : 272
 Current (A) : 3
 Voltage (V) : 220-240
 Frequency (Hz) : 50
 Plug type : Gardy plug w/ earthing
 Installation typology : Half-integrated
 Material body : Stainless steel
 Approval certificates : CE, VDE
 Plug type : Gardy plug w/ earthing
 Dimensions of the packed product (in) : 14.56 x 31.49 x 18.11
 Net weight (lbs) : 20
 Gross weight (lbs) : 29
 Motor location : Integrated motor in hood body
 No-return airflow flap : Yes
 Length electrical supply cord (cm) : 100
 Dimensions of the product, with chimney (if exists) (mm) : 418 x 700 x 300
 Net weight (kg) : 9.0
 Gross weight (kg) : 13.0

Gaggenau
 AC200180
 Canopy hood Serie 200

EAN code:
 4242006257491

sales programme:

Predecessor:

Successor:

AC200180
Canopy extractor 200 series
Stainless steel and glass
Width 70 cm
Air extraction/Air recirculation

