

Revision: 1

Date: March 2020

Supersedes all previous issues

3.03.1

## **Elvire Cleanflush**<sup>™</sup> **Invisi II**

4.5/3 litre Dual Flush Toilet Suite with Elvire Cleanflush™ Wall Faced Rimless Vitreous China Pan and Invisi II Cistern for Inwall, Under Counter, Induct or Inceiling applications











## Elvire Cleanflush<sup>™</sup> Invisi II

4.5/3 litre Dual Flush Toilet Suite with Elvire Cleanflush™ Vitreous China Wall Faced Rimless Pan and Invisi II Cistern for Inwall, Under Counter, Induct or Inceiling applications





Inspired by the unique nature and wilderness of Australia, the Elvire collection evokes a harmony of design, ergonomics and aesthetics. Combining a soft, natural design with rimless pan technology, the **Elvire Cleanflush™** is a superior flushing system suitable for domestic and commercial applications. Incorporating several patented technologies: Caroma Flow Splitter™, Caroma Flow Balancer™ and Caroma Uni-Orbital® Connector, the Cleanflush pan is innovative and the next evolution in toilets. The Flow Splitter evenly flows water around the top of the bowl to meet at the Flow Balancer which directs the water powerfully into the sump, reducing the need for brush cleaning. The rimless pan is easy to clean and unlike traditional pan profiles, provides full visibility of any grime build up. Caroma Cleanflush provides a cleaner clean for peace of mind.

Pan: Elvire Cleanflush™ wall faced back inlet 4.5 litre full flush rimless pan.

**Traps:** Universal trap for S or P-trap installations.

Inlet: Fully glazed 50mm back inlet for concealed cistern.

Cisterns and Invisi II Cistern – suitable for inwall, under counter, induct and inceiling applications. For push button and access plate (supplied separately) options see

chapter 6.15.1 CISTERNS of the Caroma Technical Manual.

**Fixing:** The pan can be fixed to the floor by either bedding into mortar or using the

supplied D82 Concealed Fixing Bracket.

Seats: The Elvire soft close quick release thermoset toilet seat is provided as standard

with this suite. See chapter 5.01 SEATS of the Caroma Technical Manual for

further details.

**Colours:** White only.

**Installation:** The installation of the toilet suite shall be in accordance with the normal minimum

drainline grade requirements in AS/NZS 3500.2.

**Dimensions:** All dimensions are in millimetres and are subject to normal manufacturing

variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications

without notice.

