

**RRP AUS \$379.00 NZ \$0.00** A 90cm stainless steel canopy rangehood with slide controls





## **Product Details**

Features			
Stainless steel finish	Slide controls	3 fan speed options	Auto thermal cutout safety switch
Optional carbon filter(s)	Recirculating option (Kit AR500RK)	Optional Extra Length Flue Cover (AR500FS)	



## **Product Details**

#### **Benefits**

Removes odours and steam while cooking Chef rangehoods are designed to remove unwanted odours and greasy steam during cooking, keeping the kitchen fresher and cleaner. Flexible Installation options Chef provides additional flexibility when installing your rangehood with the option to recirculate or duct

Keeping the air clean Carbon filters given the extra odour filtration required when ducted installation is not an option for your kitchen Easy to maintain Filters are easy to remove and can be washed in the dishwasher

# **Specifications**

### **PRODUCT PROFILE**

Domestic warranty details (yrs)	2
Type of Rangehood	wall mounted canopy
Design family (eline)	Chef
Nominal width	90
Finish of Rangehood	stainless steel

### **MOTOR/FAN**

Number of fans	2
Number of fans speeds	3
Variable speed control	No
Type of motor	centrifugal
Maximum airflow M3/Hr	550
Noise level dB high	55
Noise level dB low	48

10

### DIMENSIONS

Total product height (mm)	230
Total product width (mm)	900
Total product depth (mm)	500
Diameter of ducting (mm)	125
Minimum installation height from cooking surface Gas (mm)	650
Minimum installation height from cooking surface Electric (mm)	650
Maximum canopy chimney height (mm)	1240
Flue cover depth (mm)	165
Flue cover width (mm)	222

### POWER

Connection	plug
------------	------

## CONTROLS

Control panel

Safety/ display indicators

switch and slide auto thermal cutout safety switch

## FILTERS

Number of filters	2
Type of filter	multi layer stainless steel
Dishwasher safe	Yes



CHEF

## LIGHTS

Number of lights	2
Wattage of light	40
Type of light	incandescent

## DUCTING / RECIRCULATION

Ducting	yes
Top or rear duct hole	top
Recirculation option	Yes
Recirculation kit	optional accessory
Optional extension flue	Yes
Length of extension flue	1100



# **Terms and Conditions**

#### IMPORTANT

This is a guide of product dimensions only. For complete installation instructions, refer to the manual provided with product.

#### **PRODUCT INFORMATION**

The descriptors and illustrations in this publication apply to the specific products and models described as at the date of issue. Under our policy of continuous productdevelopment, product specifications may change without notice. Prospective purchasers should therefore check with their retailer to ensure this publication correctly describes theproducts that are being offered for sale. All information supplied is to be used for general reference purposes only and is on the understanding that Electrolux Home Products PtyLtd (Australia) and Electrolux (NZ) Ltd (New Zealand) will not be liable for any loss, liability or damage of whatever kind arising as a result of reliance on such information. Colours ofproducts illustrated are as close as printing limitations allow. Electrolux will at all times comply with its obligations pursuant to law including Trade Practices (Australian Consumer Law) Act and Regulations.

#### WARRANTY

This warranty only applies to Appliances purchased and used in Australia or New Zealand and used in normal domestic applications and is in addition to (and does not exclude, restrict, or modify in any way) any non-excludable statutory warranties in Australia or New Zealand. All warranties are subject to the conditions set out in the warranty card accompanying the product when purchased.

#### ELECTROLUX HOME PRODUCTS AUSTRALIA

telephone: 1300 363 640 fax: 1800 350 067 email: customercare@electrolux.com.au web: www.electrolux.com.au

#### ELECTROLUX HOME PRODUCTS NEW ZEALAND telephone: 09 573 2230 fax: 09 573 2221 email: customercare@electrolux.co.nz web: www.electrolux.co.nz