

PGA75-4

smeg 75cm topmount cooktop



linear control knobs included



EAN	8017709155353
finish	satin stainless steel cast-iron trivets & burner caps
installation	built-in one-piece hob
actual size	720mmW x 512mmD x 75mmH (excluding control knob height)
cutout	700mmW x 492mmD
capacity	37.8 mj/hr max over five burners <ul style="list-style-type: none"> • ultra-rapid triple burner, 15 mj/hr • 2 x semi-rapid burners, 7.5 mj/hr each • 2 x auxiliary burners, 3.9 mj/hr each
ignition	automatic electronic
safety	flame failure device (FFD) fitted to each burner
gas input	set for natural gas — regulator supplied adaptable for ULPG — no regulator required
accessories	3x heavy-duty cast-iron trivets, cast-iron pot rest & wok stand
option	Linear design control knobs (included)
warranty	two years parts and labour

SPACIOUS DESIGN

When space is not restrictive, this wide 72cm hob offers five burners ergonomically positioned for maximum benefit with the possibility of several styles of cooking at the one time.

ULTRA-RAPID BURNER

Centrally located, this large and versatile burner suits the larger stock pots, boilers, saucepans and griddles. A wok stand is supplied for easy fitment over the centre trivet for stir-fry cooking.

ELECTRONIC IGNITION

The cooktop is connected with a power cord of 1.3 metre length to be plugged into a GPO located according to installation needs below the benchline. This supplies a continuous stored charge to spark the gas supply to the individual burner of your choice.

FLAME FAILURE DEVICE

A flame failure device is fitted to all five burners. The FFD ensures that should a flame be extinguished accidentally, the gas supply to the specific burner(s) is stopped within four seconds. For absolute safety, the burner(s) can only be reignited by physically resetting the control knob(s) to the OFF position and then following normal ignition procedure. Simply depress and turn the control of the desired cooking zone for almost instant flame ignition.

LOW MAINTENANCE

The seamless hob design allows for easy wipe-over cleaning. The control knobs are removable for cleaning access. Trivets, burner assemblies and wok stand can be washed in warm soapy water.

CAST-IRON POT REST

This sturdy cast-iron accessory can sit on the cast-iron trivet above any burner. The extra space this pot rest creates above the simmer flame enables very controllable low heat cooking.

PGA75-4

smeg 75cm topmount cooktop

height	75mm includes trivets
width	720mm
depth	512mm
cutout	700mmW x 492mmD
packaged dimensions	820mm x 620mm x 180mm = 0.09m ³
net weight	15.7kg
gross weight	17.1kg
maximum gas input rate	<ul style="list-style-type: none"> • ½" BSP gas inlet connection • gas connection located right-hand rear corner • ½" BSP 1.0 kPa natural gas regulator is supplied with natural gas hobs • adaptable for ULPG — no regulator required
ignition supplied	1.3 metre length power cord, suitable for standard 10 amp GPO clips, seal, instructions for installation, operation, maintenance

NB drawings are not to scale — they are to assist only

