

Controls at the bottom

Right-hinged

BMP 224 100

Full glass door in Gaggenau Anthracite Width 60 cm

BMP 224 110

Full glass door in Gaggenau Metallic Width 60 cm

Left-hinged

BMP 225 100

Full glass door in Gaggenau Anthracite Width 60 cm

BMP 225 110

Full glass door in Gaggenau Metallic Width 60 cm

Included in the price

- 1 glass tray
- 1 wire rack

Microwave oven 200 series BMP 224/BMP 225

- Flush installation
- Handleless door / automatic door opening
- Single operation and combination of microwave and grill
- Sequential operation of up to 5 modes incl. programming of combined operation and rest time
- TFT touch display
- Electronic temperature control
- Interior volume 21 litres

Programmes

Microwave operation with 5 output levels: 900, 600, 360, 180, 90 W. Full surface grill with 3 levels of intensity, maximum output 1300 W. Full surface grill with microwave output levels 360, 180 and 90 W combinable. 10 automatic programmes with weight indication:

- 3 defrosting programmes
- 4 cooking programmes
- 3 combination programmes
- Option to save individual recipes.

Handling

Automatic door opening. Rotary knob and TFT touch display operation.

Clear text display in 25 languages. Information key with use indicators. Side-opening door opens up to 110° angle.

Features

Innowave.

Actual temperature display. 25 W interior light.

Hygienic stainless steel interior with glass ceramic base.

Safety

Thermally insulated door with double glazing.

Triple door lock.

Child lock.

Safety shut-off.

Cooled housing with temperature protection.

Planning notes

Door hinge not reversible. Minimum installation height 85 cm (top

edge of niche bottom).

Height-adjustable feet.

Installation of BMP above BOP with intermediate shelf.

Necessary lateral gap between appliance door and furniture panel of min. 5 mm.

When planning a corner solution, pay attention to the 90° door opening angle.


Please read the installation details regarding air ducting on page 8/9.

Connection

Total connected load 2.0 kW. Connecting cable with 10amp plug.

230-240V/50Hz

Installation in a wall-hanging cupboard



Installation in a tall cupboard

