

T56TS31N0 FLEXINDUCTION COOKTOP WITH TWISTPAD® FIRE

CONTROL



Standalone FlexInduction cooktop with TwistPad® Fire control.

- ✓ Induction - With induction cooking, the heat is generated directly in the cookware for precise cooking that stops when power is off.
- ✓ FlexInduction - The FlexZone lets you place your pots and pans anywhere you want and heats them exactly where they stand.
- ✓ The TwistPad® Fire is a removable, magnetic, illuminated control knob that gives you precise, convenient control over all cooking zones. And to make things even easier, only the selectable functions are illuminated.
- ✓ PowerMove - The FlexZone is divided into three heating zones: boiling in front, simmering in the middle and warming in the rear.
- ✓ FryingSensor - The FryingSensor with 5 selectable temperature settings monitors the set temperature and holds it steady. So there's no more burning.
- ✓ Stainless-steel flush-fitted trim

Features

Technical Data

Product name/family : Cooking zone ceramic
 Construction type : Built-in
 Energy input : Electric
 Total number of positions that can be used at the same time : 3
 Type of control setting devices : Cylindrical controls, magnetic knob, Twist pad flat
 Required niche size for installation (HxWxD) : 51 x 560-560 x 490-500
 Width of the product (mm) : 606
 Dimensions of the product (mm) : 51 x 606 x 546
 Net weight (kg) : 14.0
 Gross weight (kg) : 15.0
 Residual heat indicator : Separate
 Location of control panel : Hob front
 Basic surface material : Ceramic
 Color of surface : Black, Stainless steel
 Color of frame : Stainless steel
 Approval certificates : AENOR, CE
 Length electrical supply cord (cm) : 110
 EAN code : 4242004191797
 Electrical connection rating (W) : 7400
 Voltage (V) : 220-240
 Frequency (Hz) : 60; 50



Optional accessories

Z9410X1 : Induction roaster , Z9415X1 : Steaming rack for Induction roaster , Z9416X2 : Griddle Plate , Z9417X2 : Teppan Yaki (large) , Z9420X0 : set of 1 pot and 1 pan for induction hob , Z9442X0 : set of 3 pots + 1 pan for induction hob Z9453X0 : Pan ,

T56TS31N0

FLEXINDUCTION COOKTOP WITH TWISTPAD® FIRE

CONTROL

Features

Handling

- TwistPad® Fire

Flexibility

- Flex zone
- 3 induction zones
- Cooking zones:
 - 1 x Ø 280 mm, 2.6 KW (max. Power level 3.7 KW) Induction;
 - 1 x Ø 380 mmx210 mm, 3.3 KW (max. Power level 3.7 KW) Induction or 2 x Ø 190 mm, 2.2 KW (max. Power level 3.7 KW) Induction

Comfort & Convenience

- PotBoost function for all cooking zones
- PanBoost
- PowerMove
- FryingSensor with 5 temperature settings
- 17 power levels for each cooking zone
- Residual heat indicator: Digital 2-step
- LED display and timer with auto switch off for all cooking zones
- Automatic safety switch-off
 - Child safety lock

Design & Innovation

- Black ceramic glass with stainless steel flush-fitted trim

Technical Information

- 60 cm width
- Installation measurements: 560 mmx490 mm
- Length wire connection: 110 cm
- Min. worktop thickness: 30 mm
- 7.4 kW total connected load
- Cable included

T56TS31N0
FLEXINDUCTION COOKTOP WITH TWISTPAD® FIRE

CONTROL

Dimensioned drawings

