



### Heating Functions

- Oven with 12 heating methods: CircoTherm®, CircoTherm® Eco, Conventional heat, Top/bottom heating Eco, Hot air grilling, Full surface grill, Half width grill, Pizza setting, Bread Baking, Bottom heating, Braising, Dough proving
- Temperature range 40 °C - 275 °C
- Cavity volume: 71 net usable litres

### Design

- Illuminated ShiftControl
- Anthracite enamel cavity with 4 shelf positions

### Cleaning

- EcoClean Direct : ceiling, back panel, side liners
- EcoClean program, Bottom Clean program
- Full glass inner door - safer touch door

### Convenience

- 2.5" colour and text Display with ShiftControl
- Temperature proposal
  - Optical temperature control
  - Actual temperature display
  - Sabbath setting
- Additional functions:
  - Steam cooking function (system steamer accessory required)
- Slide&Hide® door, SoftOpen
- Electronic clock
- Rapid heating-up
- Halogen lighting
- Cooling fan
- Stainless-steel fan
- Info button
- Revolution handle

### Hook-in racks / rails

- Cavity with shelf support rails, Telescopic slide-out Accessory

### Accessories

- 2 x combination grid, 1 x universal pan

### Safety and Environment

- Individual adjustable child lock
- Residual heat indicator
- Safety switch off
- Triple glazed door

### Technical Info

- Length of mains cable: 120 cm
- Total connected load electric: 3.45 KW
- Appliance dimensions (HxWxD): 595 mm x 596 mm x 548 mm
- Installation dimensions (HxWxD): 585 mm - 595 mm x 560 mm - 568 mm x 550 mm
- Please reference the built-in dimensions provided in the installation drawing

## Oven B47CR32N0B, Stainless steel

If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness	
	fitted	flush
Induction hob	37 mm	38 mm
Full surface induction hob	43 mm	48 mm
Gas hob	32 mm	42 mm
Electric hob	22 mm	24 mm

### Characteristics

Color / Material Front : Stainless steel  
 Built-in / Free-standing : Built-in  
 Integrated Cleaning system : catalytic all sides, Hydrolytic  
 Required niche size for installation (HxWxD) : 585 x 560 x 550  
 Dimensions of the product (mm) : 595 x 596 x 548  
 Control Panel Material : Stainless steel  
 Door Material : Glass  
 Net weight (kg) : 36.0  
 Usable volume of cavity (l) : 71  
 Cooking method : , Bottom heat, Bread Baking Setting, Conventional heat, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot Air-Eco, Hot air grilling, low temperature cooking, Pizza setting  
 First cavity material : Enamelled  
 Temperature control : electronic  
 Number of interior lights : 1  
 Approval certificates : CE, VDE  
 Length electrical supply cord (cm) : 120  
 Interior Lights - cavity 1 : 1  
 Pull-out system : Accessory  
 Clock function : Alarm, Off, On  
 Included accessories cavity 1 : 2 x combination grid, 1 x universal pan  
 Broil Element Wattages cavity 1 (W) : 2800  
 Convection Element Wattages cavity 1 (W) : 2300

**Consumption and connection features**  
 Energy consumption conventional (kWh) - cavity 1 : 0.87  
 Energy consumption forced air convection (kWh) - cavity 1 : 0.69  
 Electrical connection rating (W) : 3450  
 Current (A) : 16  
 Voltage (V) : 220-240  
 Frequency (Hz) : 60; 50  
 Plug type : no plug  
 Color / Material Front : Stainless steel  
 Energy input : Electric  
 Approval certificates : CE, VDE  
 Dimensions of the packed product (in) : 26.57 x 25.98 x 27.16  
 Net weight (lbs) : 80  
 Gross weight (lbs) : 85  
 Length electrical supply cord (cm) : 120  
 Required niche size for installation (HxWxD) : 585 x 560 x 550  
 Dimensions of the product (mm) : 595 x 596 x 548  
 Net weight (kg) : 36.0

### Alternative colors available

B47CR32N0B:Stainless steel

### Optional accessories

Z11AB10A0 Baking tray, anti-adherent coating  
 Z11AU10A0 Multipurpose pan, anti-adherent coating  
 Z11CR10X0 Baking and roasting grid (standard)  
 Z11GT10X0 Glass roasting dish, 5,1l  
 Z11GU20X0 Glasspan  
 Z11SZ00X0 SeamlessCombination mounting kit  
 Z11SZ80X0 SeamlessCombination 60 + 29cm  
 Z11SZ90X0 SeamlessCombination 60 + 45cm  
 Z11TC10X0 ComfortFlex Rail (1 level)  
 Z11TC16X0 ComfortFlex Rail (1 level)  
 Z11TF36X0 3 level telescopic rails, full ext  
 Z12CB10A0 Enamelled baking tray  
 Z12CL10A0 Lid for professional pan  
 Z12CM10A0 Moussaka pan, enamelled  
 Z12CN10A0 Professional pan, enamelled  
 Z12CP10A0 Pizza tin  
 Z12CQ10A0 Grill tray, enamelled  
 Z12CU10A0 Multipurpose pan, enamelled  
 Z18C60X0 Cookbook  
 Z1913X0 Baking Stone  
 Z19DD10X0 Steam set for ovens  
 Z6390X0  
 Z9220W0 Conversion cabinet

### Included accessories

2 x combination grid  
 1 x universal pan

### EAN code

4242004181521

## Oven Technical Data