KBTAU900AE

Product family	Hood
Hood Type	Decorative wall hood
Design	T flat
Extraction	Extraction
Electronic control	Yes
Material	Painted material
Type of steel	Brushed
EAN code	8017709312978
Aesthetic	Universale
Colour	Anthracite
Logo	Silk screen

Controls

Control setting	Electronic buttons

Program / Functions

No. of speeds	3
Intensive speed	BOOST
24h air filter function	24
Time-setting options	

Technical Features

No. of lights	2	**Anti-grease filters**	Aluminium
Light type	LED	**Filter replacement indicator**	Yes
Light Power	1.3 W	**Vent outlet**	150 mm
Free outlet maximum capacity	730 m³/h	**Minimum distance from GAS hob**	650 mm
Motor power	230 W	**Minimum distance from ELECTRIC hob**	500 mm
No. of filters	3	**Non return valve**	Yes

Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dBA]

Speed 1	265	47
Speed 2	360	55
Speed 3	480	62
Intensive speed	713	72

Accessories Included

Tube reduction	Yes

Performance / Energy Label

Annual Efficiency Consumption (AEChood)	54 kWh/a
Energy efficicency class (EEC)	A
Fluid Dynamic Efficiency (FDE)	31,2
Fluid Dynamic Efficiency class (FDEC)	A
Lighting Efficiency (LE)	60,0 lux/W
Lighting Efficiency Class (LEC)	A
Grease Filtering Efficiency (GFE)	76,5 %
Grease Filtering Efficiency Class (GFEC)	C
Air flow at minumum speed (Qmin)	265 m³/h
Air flow at maximum speed (Qmax)	480 m³/h
Air flow at boost speed (Qboost)	713 m³/h

Airbourne acouistical A-weighted sound Power Emission at minimum speed (SPEmin)	46 dBA
Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax)	62 dBA
Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost)	71 dBA
Time increase factor (F)	0,9
Energy Efficiency Index	52,0
Measured air flow rate at best efficiency point (Qbep)	395 m³/h
Measured air pressure at best efficiency point (Pbep)	451 Pa
Measured electric power input at best efficiency point (Wbep)	159 W
Nominal Power consumption of the light system (WL)	3 W
Average illumination of the light on the cooking surface (Emiddle)	156 lux
Sound power level at highest setting (Lwa)	62 dBA

Electrical Connection

Plug	(I) Australia
Electrical connection rating	230 W
Voltage	220-240 V
Frequency (Hz)	50-60 Hz
Power supply cable length	1500 mm

Compatible Accessories

KITCEKBTMB



KITFCKBTR

1 pcs of Charcoal filter Regenerable* suitable for all the KBT/KBCT models. * It can be washed in the dishwasher up to 12 times and dry in the oven at max 90° for 60 min. dimension 237,5(H)x245x10 mm



KITFCKBT

1 pcs di filtro a carboni attivi per i modelli di cappe KBT* / KBCT*

Symbols glossary

24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.

A: Product drying performance, measured from A+++ to D / G depending on the product family

Warning light(s): to advise when filters need changing.

Intensive/turbo setting: when extra fast extraction is required.

Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.

Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.

Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.