

## Slimline rangehood DA 3496

### Slimline rangehood with energy-efficient LED lighting and light-touch switches for easy use.

- Elegant design - slim 90 cm pull-out canopy
- Powerful - 720 m<sup>3</sup>/h in the 'Intensive' setting
- Efficient filtration- 10 layer stainless steel grease filter
- Safe and easy to clean - Miele CleanCover
- Suitable for every home - w. extraction or recirculation function

<b>Construction type</b>	
Slimline cooker hood	•
<b>Design</b>	
Colour	Stainless steel
<b>Operating modes</b>	
Type of air guide	Convertible
<b>User convenience</b>	
Electronic controls	•
Light-touch switches with LED	•
Power levels (number excl. Intensive)	3
Intensive setting	•
Programmable 'Intensive' switch-off	•
<b>Cleaning convenience</b>	
Easy-to-clean CleanCover hood liner	•
<b>Filter system</b>	
Dishwasher-proof stainless steel grease filters	2
<b>Lighting</b>	
LED	•
Number x W	2 x 3 W
Colour temperature in K	3.000
Light intensity in Lx	300
<b>Fan</b>	
Dual-action fan	•
AC motor	•
<b>Air throughput with max. duct diameter in vented mode (not for external version)</b>	
Air throughput in setting 1 (m <sup>3</sup> /h) according to EN 61591	280
Air throughput in setting 3 (m <sup>3</sup> /h) according to EN 61591	570
Air throughput in setting 2 (m <sup>3</sup> /h) according to EN 61591	420
Air throughput in Intensive setting (m <sup>3</sup> /h) according to EN 61591	720
Noise power level in setting 1 (dB(A) re 1 pW) according to EN 60704-3	47
Noise power level in setting 2 (dB(A) re 1 pW) according to EN 60704-3	55
Noise power level in setting 3 (dB(A) re 1 pW) according to EN 60704-3	62
Noise power level in Intensive setting (dB(A) re 1 pW) according to EN 60704-3	69
Noise pressure level in setting 1 (dB(A) re 20 µPa) according to EN 60704-2-13	34
Noise pressure level in setting 2 (dB(A) re 20 µPa) according to EN 60704-2-13	41
Noise pressure level in setting 3 (dB(A) re 20 µPa) according to EN 60704-2-13	48
Noise pressure level in Intensive setting (dB(A) re 20 µPa) according to EN 60704-2-13	55

## Slimline rangehood DA 3496

<b>Air throughput in recirculation mode</b>	
Air throughput in setting 1 (m <sup>3</sup> /h) according to EN 61591	220
Air throughput in setting 2 (m <sup>3</sup> /h) according to EN 61591	320
Air throughput in setting 3 (m <sup>3</sup> /h) according to EN 61591	420
Air throughput in Intensive setting (m <sup>3</sup> /h) according to EN 61591	500
Noise power level in setting 1 (dB(A) re 1 pW) according to EN 60704-3	57
Noise power level in setting 2 (dB(A) re 1 pW) according to EN 60704-3	64
Noise power level in setting 3 (dB(A) re 1 pW) according to EN 60704-3	68
Noise power level in Intensive setting (dB(A) re 1 pW) according to EN 60704-3	71
Noise pressure level in setting 1 (dB(A) re 20 µPa) according to EN 60704-2-13	57
Noise pressure level in setting 2 (dB(A) re 20 µPa) according to EN 60704-2-13	64
Noise pressure level in setting 3 (dB(A) re 20 µPa) according to EN 60704-2-13	68
Noise pressure level in Intensive setting (dB(A) re 20 µPa) according to EN 60704-2-13	71
<b>Safety</b>	
Safety switch-off	•
<b>Technical data</b>	
Canopy width in mm	895
Height of hood carcass in mm	34
Depth of hood carcass in mm	275
Minimum distance above electric hobs in mm	450
Minimum height above gas hob (max. 12.6 kW total power, burner ? 4.5 kW) in mm	650
Net weight in kg	14,0
Length of electrical cable in m	1,5
Total connected load in kW	0,30
Voltage in V	230
Fuse rating in A	10
Number of phases	1
<b>Installation notes</b>	
Vent connection at top	•
Diameter of vent connection in mm	150
<b>Accessories supplied</b>	
Non-return flap	•