

Slimline rangehood DA 3466



Slimline rangehood with energy-efficient LED lighting and light-touch switches for easy use.

- Elegant design - slim 60 cm pull-out canopy
- Powerful - 720 m³/h in the 'Intensive' setting
- Efficient filtration- 10 layer stainless steel grease filter
- Safe and easy to clean - Miele CleanCover
- Suitable for every home - w. extraction or recirculation function

Construction type	
Slimline cooker hood	•
Design	
Colour	Stainless steel
Operating modes	
Type of air guide	Convertible
User convenience	
Electronic controls	•
Light-touch switches with LED	•
Power levels (number excl. Intensive)	3
Intensive setting	•
Programmable 'Intensive' switch-off	•
Cleaning convenience	
Easy-to-clean CleanCover hood liner	•
Filter system	
Dishwasher-proof stainless steel grease filters	1
Lighting	
LED	•
Number x W	2 x 3 W
Colour temperature in K	3.000
Light intensity in Lx	320
Fan	
Dual-action fan	•
AC motor	•
Air throughput with max. duct diameter in vented mode (not for external version)	
Air throughput in setting 1 (m³/h) according to EN 61591	280
Air throughput in setting 3 (m³/h) according to EN 61591	570
Air throughput in setting 2 (m³/h) according to EN 61591	420
Air throughput in Intensive setting (m³/h) according to EN 61591	720
Noise power level in setting 1 (dB(A) re 1 pW) according to EN 60704-3	47
Noise power level in setting 2 (dB(A) re 1 pW) according to EN 60704-3	55
Noise power level in setting 3 (dB(A) re 1 pW) according to EN 60704-3	62
Noise power level in Intensive setting (dB(A) re 1 pW) according to EN 60704-3	69
Noise pressure level in setting 1 (dB(A) re 20 µPa) according to EN 60704-2-13	34
Noise pressure level in setting 2 (dB(A) re 20 µPa) according to EN 60704-2-13	41
Noise pressure level in setting 3 (dB(A) re 20 µPa) according to EN 60704-2-13	48
Noise pressure level in Intensive setting (dB(A) re 20 µPa) according to EN 60704-2-13	55

Slimline rangehood DA 3466



Air throughput in recirculation mode	
Air throughput in setting 1 (m³/h) according to EN 61591	220
Air throughput in setting 2 (m³/h) according to EN 61591	320
Air throughput in setting 3 (m³/h) according to EN 61591	420
Air throughput in Intensive setting (m³/h) according to EN 61591	500
Noise power level in setting 1 (dB(A) re 1 pW) according to EN 60704-3	57
Noise power level in setting 2 (dB(A) re 1 pW) according to EN 60704-3	64
Noise power level in setting 3 (dB(A) re 1 pW) according to EN 60704-3	68
Noise power level in Intensive setting (dB(A) re 1 pW) according to EN 60704-3	71
Noise pressure level in setting 1 (dB(A) re 20 µPa) according to EN 60704-2-13	57
Noise pressure level in setting 2 (dB(A) re 20 µPa) according to EN 60704-2-13	64
Noise pressure level in setting 3 (dB(A) re 20 µPa) according to EN 60704-2-13	68
Noise pressure level in Intensive setting (dB(A) re 20 µPa) according to EN 60704-2-13	71
Safety	
Safety switch-off	•
Technical data	
Canopy width in mm	595
Height of hood carcass in mm	34
Depth of hood carcass in mm	275
Minimum distance above electric hobs in mm	450
Minimum height above gas hob (max. 12.6 kW total power, burner ? 4.5 kW) in mm	650
Net weight in kg	12,0
Length of electrical cable in m	1,5
Total connected load in kW	0,30
Voltage in V	230
Fuse rating in A	10
Number of phases	1
Installation notes	
Vent connection at top	•
Diameter of vent connection in mm	150
Accessories supplied	
Non-return flap	•