

## DA 399-7 Classic

Wall mounted cooker hood with energy-efficient LED lighting and light-touch switches for easy use.



- Design – 898mm wide trapezoidal canopy
- Powerful – 500m<sup>3</sup>/h on the booster setting
- Efficient filtration – 10-layer stainless-steel grease filter
- Safe and easy to clean – Miele CleanCover
- For perfect functionality – accessories for proper venting

|   |                 |
|---|-----------------|
| <b>Construction type</b>  |                 |
| Wall-mounted rangehood  | •               |
| <b>Design</b>   |                 |
| Colour  | Stainless steel |
| RAL colours available as customisation on request   | •               |
| Customisation possible on request   | •               |
| Variable height available as customisation on request                                       | •               |
| <b>Operating modes</b>  |                 |
| Type of air guide   | Convertible     |
| <b>User convenience</b>   |                 |
| Electronic controls   | •               |
| Light-touch switches with LED   | •               |
| Power levels (number without Booster level)   | 3               |
| Booster level   | •               |
| Programmable Booster level switch-off   | •               |
| <b>Cleaning convenience</b>   |                 |
| Easy-to-clean canopy interior – CleanCover  | •               |
| <b>Filter system</b>  |                 |
| Number of dishwasher safe stainless-steel grease filters (10-ply)                           | 3               |
| <b>Lighting</b>   |                 |
| LED   | •               |
| Light intensity in Lx   | 300             |
| Colour temperature in K   | 3,000           |
| <b>Fan</b>  |                 |
| Dual-action fan   | •               |
| AC motor  | •               |
| <b>Air throughput with max. duct diameter in extraction mode (not for external version)</b> |                 |
| Air throughput in Level 1 (m <sup>3</sup> /h) according to EN 61591                         | 150             |
| Air throughput in Level 2 (m <sup>3</sup> /h) according to EN 61591                         | 250             |
| Air throughput in Level 3 (m <sup>3</sup> /h) according to EN 61591                         | 350             |
| Air throughput in Booster level (m <sup>3</sup> /h) according to EN 61591                   | 500             |
| Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3                              | 41              |
| Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3                              | 47              |
| Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3                              | 55              |
| Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3                             | 62              |
| Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13                      | 26              |
| Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13                      | 34              |
| Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13                      | 40              |
| Sound power in Booster level (dB(A) re 20 µPa) acc. to EN 60704-2-13                        | 47              |

## DA 399-7 Classic


Wall mounted cooker hood with energy-efficient LED lighting and light-touch switches for easy use.



| <b>Air throughput in recirculation mode</b>                                     |      |
|---|------|
| Air throughput in Level 1 (m <sup>3</sup> /h) according to EN 61591             | 100  |
| Air throughput in Level 2 (m <sup>3</sup> /h) according to EN 61591             | 150  |
| Air throughput in Level 3 (m <sup>3</sup> /h) according to EN 61591             | 250  |
| Air throughput in Booster level (m <sup>3</sup> /h) according to EN 61591       | 350  |
| Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3                  | 48   |
| Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3                  | 55   |
| Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3                  | 61   |
| Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3                 | 68   |
| Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13          | 34   |
| Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13          | 41   |
| Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13          | 47   |
| Sound power in Booster level (dB(A) re 20 µPa) acc. to EN 60704-2-13            | 53   |
| <b>Safety</b>   |      |
| Safety switch-off   | •    |
| <b>Technical data</b>   |      |
| Overall height for extraction mode and external mode cooker hoods in mm         | 695  |
| Overall height for recirculation mode cooker hoods in mm                        | 825  |
| Canopy width in mm  | 898  |
| Canopy height in mm   | 120  |
| Canopy depth in mm  | 520  |
| Minimum height above electric hobs in mm  | 450  |
| Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm | 650  |
| Net weight in kg  | 26.0 |
| Length of supply lead in m  | 1.5  |
| Standard plug fitted  | •    |
| Total rated load in kW  | 0.13 |
| Voltage in V  | 230  |
| Fuse rating in A  | 10   |
| Number of phases  | 1    |
| <b>Installation notes</b>   |      |
| Extraction ducting connection at top  | •    |
| Extraction connection at top and rear   | •    |
| Diameter of extraction ducting connection in mm                                 | 150  |
| Telescopic chimney  | •    |
| <b>Standard accessories</b>   |      |
| Non-return flap   | •    |

## DA 399-7 Classic

Wall mounted cooker hood  
with energy-efficient LED lighting and light-touch switches for easy use.



DA 399-6 (Installation drawing)

- 1) Extraction
- 2) Recirculation
- 3) Ventilation grille at top for recirculation
- 4+5) Installation cut-out (5 not required for recirculation)