

OR90SCI6W1 Freestanding Induction Cooker, 90cm

Classic

Designed for perfect multi-shelf cooking, this 90cm Fisher & Paykel Freestanding Induction Cooker lets you cook several dishes at the same time with its spacious induction cooktop and large capacity, self-cleaning convection oven. With heritage styling and a white finish, this Cooker becomes the centrepiece of the kitchen.

White



A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support T 1300 650 590 W www.fisherpaykel.com

Dimensions

| Depth | 600mm |
|--------|-------------|
| Height | 898 - 946mm |
| Width | 897mm |

Features & Benefits

Multi-shelf cooking

Our AeroTech[™] system circulates air evenly throughout the entire oven so dishes on the top shelf turn out just as perfect as food cooking on the bottom shelf.

Quality and durability

Every detail has been carefully crafted. The solid, perfectly balanced soft-close door, durable cooktop and glowing halo dials all add up to an exceptional, premium range.

Power & control

Instant and immediate control from the highest to the gentlest heat. The finely tuned cooktop controls let you sear, stir fry or simmer a delicate sauce to perfection.

Easy to clean

Cleaning up spills is effortless. Your cooktop simply needs a quick wipe to keep it looking good as new. The pyrolytic self-clean oven cycle breaks down food residue at a very high temperature, leaving a light ash that's easily removed with a damp cloth.

Even heat

Accurate, electronically-controlled oven heat ensures a great result every time.

Large capacity oven

The generous 140L total capacity oven gives you plenty of space to cook multiple dishes at once.

Specifications

| Accessories | |
|--|----------------------|
| Flat wire shelf | 1 |
| Full extension sliding shelves | 2 sets (part 578744) |
| Grill rack | • |
| Kick strip, stainless steel (optional) | Part 81661 |
| Kick strip, white (optional) | Part 81768 |
| Pyrolytic proof shelf runners | 1 set |
| Roasting dish | • |
| Rotisserie set | 1 |
| Step down wire shelf | 1 |
| Cleaning | |
| Acid resistant graphite enamel | • |
| Drop down grill element | • |
| Flat easy clean glass surface | • |

Pyrolytic Self-clean Pyrolytic proof shelf runners

Removable oven door inner glass

Removable oven door/s

Removable shelf runners

SPEC SHEET > OR90SCI6W1 > Freestanding Induction Cooker, 90cm

| Controls | |
|---|--|
| Audio feedback | |
| Automatic cooking/minute timer | |
| Automatic pre-set temperatures | |
| Bright chromed, cast zinc dials with | |
| illuminated halos | |
| Celsius/Fahrenheit temperature | |
| Electronic clock | |
| High resolution display | |
| Interior light | |
| Laser etched graphics | |
| Precise electronic temperature control | |
| Sabbath mode | |
| Toughened fused glass graphics | |
| Turned stainless steel clock buttons | |
| Turned stainless steel clock crown (dial) | |

Cooktop features

| Auto heat reduce | • |
|--------------------------------|--------------------------|
| Dual colour display | • |
| Gentle heat | 2 settings (42°C & 65°C) |
| Heat settings | 9 |
| Hob rail | • |
| Hob rear trim | 60 mm |
| Induction cooking technology | • |
| PowerBoost | • |
| PowerBoost all Zones | • |
| SmartZone | • |
| Zone bridging | • |
| Installation cutout dimensions | |
| Depth | 600 mm |
| Width | 900 mm |
| | |

Oven features AeroTech[™] technology Automatic rapid pre-heat Electronic oven control Full extension telescopic sliding shelves 2 sets [part 578744) 4 x 25W halogen (2 side & Internal light 2 top) Pyrolytic Self-clean Pyrolytic proof shelf runners Soft open/close door True Convection Twin cavity fans Warming drawer **Oven functions** Bake Fan Bake Fan Forced Fan grill Grill 9 + rotisserie Number of Functions Pastry Bake with Pizza mode Pyrolytic Self-clean Rapid Proof Roast Rotisserie

| Date: 30.07.2019 > |
|--------------------|
|--------------------|

| Oven performance | |
|---|------------------|
| CoolTouch door | Quadruple glazed |
| Grill | 4500 W |
| Shelf positions | 6 |
| Total oven capacity | 140 L |
| Usable capacity | 121 L |
| Warming drawer | 202 W |
| Power requirements | |
| AMP draw | 68 A |
| Supply frequency | 50 Hz |
| Supply voltage | 220 - 240 V |
| Safety | |
| Advanced cooling system | • |
| Anti-tilt bracket | • |
| Balanced oven door | • |
| Catalytic venting system | • |
| Child lock | • |
| CoolTouch door | • |
| Full extension telescopic sliding shelves | • |
| Non-tip shelves | • |
| Pan detection system | • |
| Safety time out | • |
| Spill containment | 1.2L |
| Spillage auto off | • |
| Spinage duto on | |
| Surface hot indicators | • |

| Warranty | |
|--------------|---------|
| Warranty | 2 years |
| Zone ratings | |
| Centre | 2300W |
| Left front | 1600W |
| Left rear | 2100W |
| PowerBoost | 3000W |
| Right front | 1600W |
| Right rear | 2100W |

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2019

Other product downloads available at fisherpaykel.com

www.fisherpaykel.com

Product Style

Classic