

Color Variants

BOP221112

Full glass door in Gaggenau Metallic Width 60 cm

BOP221102

Full glass door in Gaggenau Anthracite Width 60 cm

Included accessories

1 x enamel baking tray. suit. pyrolitic clean. 1 x glass pan. 1 x grill shelf.

Optional accessories

BA016105

Pull-out system for 60cm ovens

BA056115

Heating element for baking stone and Gastronorm roaster.

BA056133

Baking stone

GN340230

Gastronorm roaster in cast aluminium.

BOP221112 Oven 200 series

Full glass door in Gaggenau Metallic

Width 60 cm

Left-hinged

Flush installation Pyrolytic system 9 heating methods, with baking stone function TFT touch display Panel-free appliance with surface control module Electronic temperature control from

50 °C to 300 °C

Net volume 76 litres

Heating methods Hot air. Eco hot air. Top + bottom heat. Top heat. Bottom heat. Hot air + bottom heat. Full surface grill + circulated air. Full surface grill. Baking stone function.

Handling

Rotary knob and TFT touch display operation. Clear text display. Option to save individual recipes. Information key with use indicators. Side-opening door opens up to 110°

Features

Baking stone socket. Actual temperature display. Rapid heating.

Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.

60 W halogen light on the top. Enamelled side shelf supports with 4 tray levels, pyrolysis-safe.

Home network integration for digital services (Home Connect) either via cable connection LAN (recommended) or wireless via WiFi.

The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: homeconnect.com.

Safety

Thermally insulated door with quintuple glazing. Child lock Safety shut-off. Cooled housing with temperature protection.

Cleaning

Pyrolytic system. Gaggenau enamel. Heated catalyser to clean the oven air.

Planning notes

Door hinge not reversible The door panel surface of the appliance extends 21 mm from the furniture cavity.

The outer edge of the door handle extends 72 mm from the furniture cavity.

Necessary lateral gap between appliance door and furniture panel of min. 5 mm.

Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.

When planning a corner solution, pay attention to the 110° door opening angle.

Characteristics

Color / Material Front

Stainless steel

Built-in / Free-standing

Built-in Integrated Cleaning system

Pyrolytic

Required niche size for installation (HxWxD)

590-590 x 560-560 x 550

Dimensions of the product (mm) 595 x 590 x 547

Dimensions of the packed product (HxWxD) (mm)

Control Panel Material

without panel Door Material

Glass

Net weight (kg)

54.654

Usable volume of cavity (I)

Cooking method

Baking stone function, Bottom heat, Conventional heat, Full width grill, Hot Air, Hot air and 1/1 bottom heating, Hot Air-Eco, Hot air grilling, Top heat

First cavity material

Enamelled

Temperature control

electronic

Number of interior lights

Approval certificates

Length electrical supply cord (cm)

EAN code

4242006279905

Consumption and connection features

Number of cavities (2010/30/EC)

Energy efficiency class (2010/30/EC)

Energy consumption per cycle conventional (2010/30/EC)

Energy consumption gas oven per cycle conventional (2010/30/EC)

Energy consumption per cycle forced air convection (2010/30/EC) 0.83

Energy consumption gas oven per cycle forced air convection (2010/30/EC)

Energy efficiency index (2010/30/EC)

Connection Rating (W)

3700 Current (A)

Voltage (V) 220-240

Frequency (Hz)

Plug type fixed connection, no plug

2019-07-10 Page 1

For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account.

To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.

The mains socket needs to be planned outside the built-in niche.

The LAN port can be found at the back on the upper right side.

Connection

Total connected load 3.7 kW. Plan a connection cable. Plan a LAN cable.



BOP221112 Oven 200 series Full glass door in Gaggenau Metallic Width 60 cm Left-hinged

2019-07-10 Page 2



