

Dishwasher 400 series
400 series
Fully integrated
With flexible hinge
DF481562F



- Optimal protection for sensitive glassware by low temperature drying with zeolite and intelligent water softening
- 8 programmes with aqua sensor and 6 options, such as Power and Intensive:
- Clean and dry dishes in 80 minutes
- Intensive cleaning in the lower basket while protecting glassware in the upper basket
- Flexible basket system with smooth running rails on all levels and cushioned closing of the upper and lower basket

[Technical specifications](#) [Downloads](#)

Additional information

Handling

- TFT display indicating remaining or end time, refill for salt and rinsing agent, inflow of water.
- Touch key operation.
- Information key with use indications.
- Time delay up to 24 hours.
- Visual and acoustic end of programme indicator.
- Info-Light.

Technical Features

- Perfectly illuminated interior.
- Glass protection with zeolite.
- Aqua sensor.
- Load sensor.
- Automatic detergent function.
- Heat exchanger.
- Continuous flow heater.
- Triple filter system.
- Soft lock.
- Aqua stop.

Programmes

- 8 programmes:
Auto 35 °C - 45 °C.
Auto 45 °C - 65 °C.
Auto 65 °C - 75 °C.
Intensive 70 °C.
Standard Eco 45 °C.
Night programme.
Quick wash 45 °C (29 min.).
Pre-rinse.
- 6 options:
Intensive.
Power.
Half Load.
Hygiene.
Extra Dry.
Shine and Dry.

Features

- Flexible basket system with smooth running rails on all levels and cushioned closing of the upper and lower basket.
- Upper basket:
Over extension.
Rackmatic with 3 levels, adjustable in height up to 5 cm.
6 folding spines.
4 folding racks.
2 glass support bars.
- Lower basket:
8 folding spines.
2 folding racks.
Dividable glass support.
- Cutlery basket.
- Holder for long-stemmed glasses.
- Maximum dish sizes (upper/lower basket)
29/28, 26.5/30.5 or 24/34 cm respectively.
- 14 place setting capacity.
- Maximum glass loading capacity 23 wine glasses.

Consumption data

- 4 Star energy rating, 4.5 Star WELS water rating
- 12 L water consumption per wash.
- From 0.62 kwh.
- Noise level 43 dB (re 1 pW).

Planning notes

- Height-adjustable feet.
- Appliance plinth recess 100 mm (see drawing).
- Rear feet adjustable at front.
- Door weight up to 11 kg.
- Door panel dimension dependent on plinth height of kitchen furniture.
- Installation and usage also with furniture handle possible. The push-to-open function remains active.




Connection

- Total connected load 2.4 kW.
- Connecting cable pluggable.
- Water connection with 3/4" screw joint.
- Connection to hot or cold water possible.




Additional information

General

Width of the product (mm)598 mm

Height of the product (mm)	865 mm
Installation typology	Full-integrated
Number of place settings	14
Water consumption (l)	12.0 l
Total annual energy consumption	136.9 kWh
List of programmes	Auto 35-45°C, Auto 45-65°C, Auto 65-75°C, Economy, Intensive, night program, Pre-Rinse, Quick wash
Additional operational options	brilliant dry, Extra dry, half load, HygienePlus, Intensive Zone, VarioSpeed
Digital countdown indicator	
Noise level (dB)	43
3rd Rack	3rd Rack 2.1
Interior light	
Removable top	
Length electrical supply cord (cm)	175 cm
Length outlet hose (cm)	190 cm

— Construction type

Color / Material panel	Grey
Construction type	Built-in
Door panel options	Not possible
Height of the product (mm)	865 mm
Hidden heating element	
Installation typology	Full-integrated
Removable top	
Tub material	Stainless steel
Water softener (permanently deactivated/disabled)	
Width of the product (mm)	598 mm

— Size and weight



Height of removable worktop (mm)	0 mm
Number of Options	6
Adjustable plinth	both horizontal and vertical
Net weight (kg)	54.134 kg

— Programmes


Drying progress indicator	End of program audible, InfoLight red, water inlet
List of programmes	Auto 35-45°C, Auto 45-65°C, Auto 65-75°C,

	Economy, Intensive, night program, Pre-Rinse, Quick wash
Name, programme 1	Auto
Name, programme 2	Auto
Name, programme 3	Auto
Name, programme 4	Intensive
Name, programme 5	Economy
Name, programme 6	night program
Programme duration, programme1 (min.)	85-95
Programme duration, programme2 (min.)	105-175
Programme duration, programme3 (min.)	105-140
Programme duration, programme4 (min.)	135-140
Programme duration, programme5 (min.)	160
Programme duration, programme6 (min.)	235
Reference programme	Eco
Number of different wash temperatures	6
Temperature, programme 1 (°C)	35-45
Temperature, programme 2 (°C)	45-65
Temperature, programme 3 (°C)	65-75
Temperature, programme 4 (°C)	70
Temperature, programme 5 (°C)	45
Temperature, programme 6 (°C)	50

— Safety

Glass protection techn.	
Surge-back protect. installed	
Water protection system	Total system

— Consumption values

Glass protection techn.	
Total annual energy consumption	136.9 kWh
Energy consumption (kWh)	0.62 kWh
Energy consumption, programme1 (kWh)	0.7-85
Energy consumption, programme2 (kWh)	0.8-1.3

Energy consumption, programme3 (kWh)	1-1.3
Energy consumption, programme4 (kWh)	1.25-1.3
Energy consumption, programme5 (kWh)	0.62
Energy consumption, programme6 (kWh)	0.8
Water consumption, programme 1 (l)	10-15
Water consumption, programme 2 (l)	7-18
Water consumption, programme 3 (l)	11-15
Water consumption, programme 4 (l)	12-15
Water consumption, programme 5 (l)	12
Water consumption, programme 6 (l)	10
Water consumption (l)	12.0 l
Maximum temperature for water intake (°C)	60 °C

Connection

Connection Rating (W)	2,400 W
Length electrical supply cord (cm)	175 cm
Current (A)	10 A
Length inlet hose (cm)	165 cm
Length outlet hose (cm)	190 cm
Plug type	AU plug

Accessories