



Color Variants

VI262120
Black anodized control panel in aluminium
Width 60 cm

Included accessories

1 x glass scraper.

Optional accessories

GP900003
Stainless steel frying sensor pan

Installation Accessories

VV200010
Stainless steel connection strip for combination with other Vario appliances of the 200 series
VV200020
Black connection strip for combination with other Vario appliances of the 200 series

VI262120
Vario flex induction cooktop 200 series
Black anodized control panel in aluminium
Width 60 cm

Can be combined with the cooktops of the Vario 200 series to a harmonic unity
Control panel for comfortable and secure operation

Cooking zones

2 flex induction cooking areas 19x23 cm (2200 W, with booster 3700 W), linked together 38x23 cm (3300 W, with booster 3700 W).
2 flex induction cooking areas 19x23 cm (2200 W, with booster 3700 W), linked together 38x23 cm (3300 W, with booster 3700 W).

Handling

Control knobs with illuminated ring.
Integrated control panel.
Electronic power control in 9 output levels.

Features

Cooking area marking.
Flex function for rectangular cooking areas.
Frying sensor function.
Pot detection.
Booster function for each cooking area.

Safety

Residual heat indication.
Operation indicator.
Safety shut-off.

Planning notes

Operates with magnetic (induction) iron pots and pans only. For an optimal heat distribution, the use of sandwich bottom cookware is recommended.
Appliance can be snapped into the worktop from above.
Appliance weight: approx. 17 kg.

Connection

Total connected load 7.4 kW.
Connecting cable 1.5 m without plug.

Characteristics

Product name/family
Cooking zone ceramic
Construction type
Built-in
Energy input
Electric
Total number of positions that can be used at the same time
4
Type of control setting devices
Required niche size for installation (HxWxD)
50 x 560-560 x 492-492
Width of the product (mm)
580
Dimensions of the product (mm)
50 x 580 x 512
Dimensions of the packed product (HxWxD) (mm)
200 x 690 x 600
Net weight (kg)
16.613
Gross weight (kg)
17.0
Residual heat indicator
Separate
Location of control panel
Hob front
Type of external control possibility
Basic surface material
Ceramic
Color of surface
Black, Stainless steel
Color of frame
Stainless steel
Approval certificates
AENOR, CE
Length electrical supply cord (cm)
150
EAN code
4242006280505

Consumption and connection features

Electrical connection rating (W)
7400
Gas connection rating (W)
Current (A)
Voltage (V)
220-240
Frequency (Hz)
50; 60

2019-07-10
Page 1

VI262120
Vario flex induction cooktop 200 series
Black anodized control panel in
aluminium
Width 60 cm

2019-07-10
Page 2

