



Evolution® 200

Category Benefits

- Food waste is ground into particles and flushed away in seconds
- Clean, hygienic, convenient and simple to use
- Easy method to manage food waste in the home, saving you time and helping to minimise trips to the outside dustbin
- Permanent in-house solution that is compact and sits under the sink without taking up valuable storage
- Easy to install into new or existing kitchens and can be fitted to most sinks
- Environmentally responsible, helping reduce the amount of waste that goes to landfill sites

Features

- Evolution ultra-quiet technology
- Evolution 3-stage grind technology
- Auto-reverse grinding action
- High-torque Dura-Drive™ induction motor
- Built-in air switch with chrome button
- 6 Year guarantee
- Stainless steel grind elements and grind chamber
- Overload protection
- Quick Lock® mounting assembly for faster, easier installation

Sample Specification

Food waste disposer(s) shall be InSinkErator® Model Evolution 200 with 3-stage grind and ultra-quiet technologies, 1 hp (110-120V) or .75 hp (220-240V) motor, auto-reverse grind system, stainless steel grind chamber, grinding elements and built-in air switch in chrome.

Guarantee: 6 Year parts and service.


The complete InSinkErator guarantee is included in the Care & Use Booklet packed with each unit.

Daten reed operation



For those who prefer the on/off switch built right into the disposer cover, InSinkErator offers the cover control accessory. It's just right for efficient batch feed operation. (Not available in all markets)

Dimensions (cm)



Evolution 200				
Α	33.0	D	23.4	
В	18.5	Ε	16.8	
С	6.4			

InSinkErator reserves the right to change product specifications without prior notice. The disposer described in this leaflet is for household use: usage in commercial situations is not covered by warranty.

Specifications

Type of Feed	Continuous	
On/Off Control	Wall Switch or Built-In Air Switch	
Motor	Single Phase	
Reversing	Auto-Reverse Grind System	
Time Rating	Intermittent	
Lubrication	Permanently Lubricated Upper & Lower Bearings	
Shipping Weight (Approx.)	11.4 kg	
Unit Finish	Stainless Steel Light Gray	
Overall Height	33.0 cm	
Grind Technology	3-Stage Grind Technology	
	Jam Preventing Circuit	

Sound Technology	Anti-Vibration Mounting and Tailpipe
	Quiet Sink Baffle
	Multi-Layer Sound Insulation
	Premium Stainless Steel Stopper
Grind Chamber Capacity	1180 ml
Motor Protection	Manual Reset Overload
Average Water Usage	Approximately 4.0 L per Person per Day
Average Electrical Usage	3-4 KWH per Annum
Drain Connection	1-1/2" (3.81 cm) Anti-Vibration (Hose Clamp)
Dishwasher Drain Connection	Yes

Volts/Hz	HP	Average Load
120V, 60 Hz	1.0	10.2 A
220-240V. 50-60 Hz	.75 (@240V/50Hz)	370 W

