ZIP HYDROTAP BC

Order Code HT1784

Zip HydroTap Boiling, Chilled, Filtered water appliance featuring a single under bench command centre including full colour interactive touch screen display with pin code protection, 2 boiling water safety modes, 3 energy saving modes including sensor activated "sleep when its dark" and 0.2 micron water filtration.

Manufacturing Code	1214AU0H0ZN1R
Capacity	Residential
Disability Options	Available

Tap	Zip HydroTap CLASSIC Tap (Chrome)
Water Pressure	Min 172kPa - Max 700kPa
Water Connection	12.7mm BSP
Water Supply Requirements	Cold
Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
Power Rating	1.55kW 220-240V 50 Hz
Power Supply	1 x 10Amp GPO
Dimensions	H333mm x W280mm x D455mm
Product Approvals	WaterMark, CE, RCM, ARC
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.
3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.
4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com

PDF DWG


Table - Zip BOM (Assembly)
∅35 Hole for G4 Tap
Position the Tap such that it dispenses into the sink bowl with ample clearance for a cup or a tea pot. Alternatively, the Tap could be mounted away from the sink using a Zip Font available as an accessory.
∅46
Sink shown only
See Detail B
43 max.
5
326
B. Cabinet Floor Cut-Out
4 min. Buffer Pad Clear Gap
116 CL reach
232
308
6
104
∅219
DETAIL FONT SCALE 1 : 5
209
126
A
Clearance Envelope
200 min
333
Mains cold water isolation valve (not supplied)
240 - 230V, 50Hz GPO
Inlet Vent
50 min.
280
50min.
A
Clearance Envelope
455
SECTION A-A SCALE 1 : 5
∅219 circumference
∅35 hole for tap tubes
83
21
60
∅108 hole for bowl
∅10 cut-away for 6mm fastening stud
Zip Industries