

Freshness For Healthy Living









2.4" Touchscreen Display: Located behind the appliance door, this high-resolution and high-contrast 2.4" touchscreen display can be read from any angle. Stored menu options are Intuitive and easy-to-operate.



BioFresh: When stored at Biofresh's precisely maintained temperature of 0°C and correct humidity level, nutrients in your food are retained. Our BioFresh drawers fully extend on telescopic rails and feature a self-closing mechanism.



PowerCooling: A high-performance system that allows freshly stored items to be chilled rapidly while maintaining an even temperature throughout the interior. In this energy-efficient BluPerformance range, the fan switches off when the appliance door is opened, saving valuable energy.


An all-round carefree package for your food: the **SBSes 8474** freestanding Side-by-Side fridge-freezer. From our BluPerformance range, this appliance combines perfect cooling performance for long-lasting freshness, ample storage space, and a classic design.

All its five BioFresh drawers run on telescopic rails and provide optimal storage conditions for your groceries at a temperature of just above 0°C in combination with ideal humidity. Our IceMaker has a fixed water connection and provides ice cubes for every occasion. The SuperCool and SuperFrost functions allow food to be cooled or frozen quickly. And if you need extra storage space, VarioSpace makes it possible.

SBSes 8474	Bio	No	lce	Soft	Soft	Smart
Premium	Fresh	Frost	Maker	System	Telescopic	Steel


Side-by-Sides comprised of two models	SBNes 4265	SKBes 4350
nergy consumption (kWh/yr) I Star rating	204 5.5	194 4.0
Compressors	1	1
otal Usable Litres	298	367
efrigerator Usable Litres	172	234
reezer Usable Litres	126	-
ioFresh Usable Litres	Included above	133
Control system and display Child proof 2	2.4"Touch display Yes	2.4"Touch display Yes
remiumPlus lighting	Yes	Yes
abbath mode	Yes	Yes
luoCooling	Yes	-
oftSystem hinge - assists closure	Yes	Yes
loor open I Temperature : alarms	Yes Yes	Yes I -
ioFresh drawers on telescopic rails	2	3
uperCool VarioSafe	- -	Yes Yes
uperFrost VarioSpace	Yes Yes	- -
ntegrated bottle shelf	-	Yes
reezer drawers I Ice cube drawer	4 1	- -
ceMaker Ice cube capacity (kg/24h)	Yes 1.2	- -
tainless steel hose supplied (m)	1.5	-
tainless steel with SmartSteel Doors Walls	Yes Yes	Yes Yes
lefault hinge	Left	Right
oltage (V) Rated Current (A)	220 - 240 1.4	220 - 240 1.2
fade in	Germany	Germany

Installation Diagram



1 To achieve the indicated energy consumption level, the wall spacers provided with the appliance must be used. This increases the appliance depth by approximately 1.5 cm. If the wall spacers are not used, the appliance will remain fully functional, but will have a slightly higher energy consumption level.

Water Connection



Plumbing must be installed adjacent to the side of the appliance which contains the IceMaker. Water pressure must be between 0.15 MPa and 0.6 MPa (1.5 bar - 6 bar)

Important information: For Side-by-Side installation the freezer or the appliance with freezer compartment must be installed on the left as viewed from the front to prevent possible formation of condensation.

Note: Whilst every effort is made to ensure all specifications and information in this flyer are accurate, Liebherr reserves the right to make changes without notification. Where actual appliance measurements, specifications, and ratings are crucial, we recommend that the actual appliance installation instructions that accompany each appliance be checked. Liebherr will not be liable for any loss.

home.liebherr.com.au