

iQ700, Integrated rangehood, 86 cm, Stainless steel LB89586AU



The powerful canopy rangehood is concealed above the cooktop.

- ✓ The highly efficient 800 m³/h extraction rate provides ideal air quality in the kitchen.
- ✓ The energy saving LED lighting with dimmer function ensures ambient lighting and optimal visibility when cooking.
- ✓ The intensive setting temporarily increases the extraction rate when kitchen vapour is especially intense, with automatic revert to previous setting after 6 min.
- ✓ Whisper quiet operation: only 55 dB (380 m³/h) - 150mm ducted.

Features

Technical Data

Typology : Traditional
 Approval certificates : Australia Standards, CE, VDE
 Length electrical supply cord (cm) : 150
 Required niche size for installation (HxWxD) : 418mm x 836.0mm x 264mm
 Minimum distance above an electric hob : 500
 Minimum distance above a gas hob : 650
 Net weight (kg) : 9.255
 Type of control : Electronic
 Maximum output air extraction (m³/h) : 610
 Boost position output recirculating (m³/h) : 380.0
 Boost position air extraction (m³/h) : 800
 Number of lights : 2
 Noise level (dB) : 64
 Diameter of air outlet (mm) : 120 / 150
 Grease filter material : Washable aluminium
 EAN code : 4242003848241
 Connection Rating (W) : 172
 Current (A) : 3
 Voltage (V) : 220-240
 Frequency (Hz) : 50
 Plug type : AU plug
 Installation typology : Built-in

Optional accessories

LZ55750	Standard recirculation kit
LZ55651	Standard odor filter (replacement)
LZ46810	CleanAir active carbon filter



iQ700, Integrated rangehood, 86 cm, Stainless steel LB89586AU

Features

Design & Innovation

- Appliance colour: Stainless steel
- Electronic controls with low-lift push buttons
- 2 x 1 Watt LED lights
- metal grease filters with stainless steel cover

Convenience

- For installation in a kitchen cabinet
- Saturation display for filters

Power and Mode of Operation

- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use 610 m³/h
- Intensive 800 m³/h
- Extraction rate in recirculation mode:
- Max. normal use: 310 m³/h
- Intensive: 380 m³/h
- 3 power levels plus intensive setting
- Intensive operation automatic revert - 6min
- Automatic run on for Automatic run on time - 30 min
- Rim ventilation
- Efficient BLDC technology
- Suitable for ducted and re-circulating operation

Cleaning

- Dishwasher safe metal grease filters
- Cassette with alu frame
- Noise level according to EN 60704-3 und EN 60704-2-13 exhaust air:
- Max. normal use: 64 dB(A) re 1 pW (51 dB(A) re 20 µPa sound pressure)
- Intensive: 70 dB(A) re 1 pW (57 dB(A) re 20 µPa sound pressure)
- with one-way flap

Technical Information

- Built-in dimensions: width: 84 cm, depth: 26 cm
- Dimensions exhaust air (HxWxD): 418-418 x 860 x 282 mm
- 120 or 150 mm tube connection diameter
- Power rating: 172 W
- Electrical cable length 1.5 m
- Accessories required for recirculation mode: CleanAir Module
- Average Energy Consumption: 25.5 kWh/year