

iQ700, Wall-mounted rangehood, 90 cm, Stainless steel LC91BUV50A



The wall hood convinces with a very high extraction rate in a distinguished design that perfectly matches your kitchen.

- ✓ Touch Control – thanks to the integrated flat surface control panel, adjustments can be easily made with just one finger
- ✓ Impressive extraction rate (964 m³/h) for efficient odour and steam removal.
- ✓ The power level of your hood can be adjusted by your cooktop
- ✓ The hood adapts the level of steam automatically matching the amount of steam and odours.
- ✓ LED light: Optimal visibility and atmosphere when cooking.
- ✓ Extremely quiet when being used (64 db(A)).

Features

Technical Data

Typology : Chimney
 Approval certificates : Australia Standards, VDE
 Length electrical supply cord (cm) : 130
 Height of product, without chimney (mm) : 46
 Minimum distance above an electric hob : 550
 Minimum distance above a gas hob : 650
 Net weight (kg) : 19.907
 Type of control : Electronic
 Number of speed settings : 3-stage + 2 intensive
 Maximum output air extraction (m³/h) : 602
 Boost position output recirculating (m³/h) : 428.0
 Boost position air extraction (m³/h) : 964
 Number of lights : 3
 Noise level (dB) : 64
 Diameter of air outlet (mm) : 120 / 150
 Grease filter material : Washable stainless steel
 EAN code : 4242003835326
 Connection Rating (W) : 269
 Current (A) : 10
 Voltage (V) : 220-240
 Frequency (Hz) : 50; 60
 Plug type : AU plug
 Installation typology : Wall-mounted

Optional accessories

LZ57300	cleanAir Recirculation Kit
LZ56200	CleanAir active carbon filter spare part
LZ53451	Standard odor filter (replacement)
LZ53450	Standard recirculation kit



iQ700, Wall-mounted rangehood, 90 cm, Stainless steel LC91BUV50A

Features

Design & Innovation

- Box brand design
- Suitable for ducted and re-circulating operation
- Accessories required for recirculation mode: CleanAir Module
- 3 x 3W LED lights

Convenience

- Wall mounted rangehood
- softLight with dimming function
- lightControl white LED control panel
- Boost function
- climateControl sensor automatically adjusts the rangehood power level to the steam and odours
- Saturation display for filters
- Dishwasher safe metal grease filters
- Stainless steel filter covers, dishwasher safe

Power and Mode of Operation

- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use 601 m³/h
- Intensive 964 m³/h
- Extraction rate in recirculation mode:
- Max. normal use: 362 m³/h
- Intensive: 428 m³/h
- 3 power levels + 2 intensive levels
- Intensive operation automatic revert - 6min
- Automatic run on for Automatic run on - 10 min
- Noise min./max. Normal Level: 45/64 dB
- Noise max. Intensive setting: 73 dB
- Efficient BLDC technology
- cooktop-based hood control
- (with matching cooktop)
- Sound insulation mats for optimised sound absorption
- with one-way flap

Technical Information

- wall fixing system
- Dimensions exhaust air (HxWxD): 628-954 x 898 x 500 mm
- Dimensions recirculating (HxWxD): 628-1064 x 898 x 500 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Power rating: 269 W
- Electrical cable length 1.3 m
- Voltage: 220 - 240 V
- Energy Efficiency Class: A+ (at a range of energy efficiency classes from A++ to E)