



BOP251102
Oven 200 series
Full glass door in Gaggenau Anthracite
Width 60 cm
left-hinged
Controls at the top

Flush installation
Pyrolytic system
13 heating methods, with core temperature probe and baking stone function
Automatic programs
TFT touch display
Panel-free appliance with surface control module
Electronic temperature control from 30 °C to 300 °C
Net volume 76 litres

Heating methods

Hot air.
 Eco hot air.
 Top + bottom heat.
 Top heat.
 Bottom heat.
 Hot air + bottom heat.
 Full surface grill + circulated air.
 Full surface grill.
 Compact grill.
 Baking stone function.
 Roaster function.
 Dough proofing.
 Defrosting.

Handling

Rotary knob and TFT touch display operation.
 Clear text display in multiple languages.
 Option to save individual recipes (incl. core temperature probe).
 Personalisation of automatic programs.
 Information key with use indicators.
 Side-opening door opens up to 110° angle.

Features

Three-point core temperature probe with automatic shut-off and estimation of cooking time.
 Automatic programs.
 Baking stone socket.
 Actual temperature display.
 Rapid heating.
 Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.
 60 W halogen light on the top.
 Enamelled side shelf supports with 4 tray levels, pyrolysis-safe.
 Home network integration for digital services (Home Connect) either via cable connection LAN (recommended) or wireless via WiFi.
 The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-connect.com.

Safety

Thermally insulated door with quintuple glazing.
 Child lock.
 Safety shut-off.
 Cooled housing with temperature protection.

Cleaning

Pyrolytic system.
 Gaggenau enamel.
 Heated catalyser to clean the oven air.

Planning notes

Door hinge not reversible.
 The door panel surface of the appliance extends 21 mm from the furniture cavity.

Characteristics

Color / Material Front
 Anthracite
Built-in / Free-standing
 Built-in
Integrated Cleaning system
 Pyrolytic
Required niche size for installation (HxWxD)
 590-590 x 560-560 x 550
Dimensions of the product (mm)
 595 x 590 x 547
Dimensions of the packed product (HxWxD) (mm)
 760 x 700 x 650
Control Panel Material
 Glass
Door Material
 Glass
Net weight (kg)
 54.893
Usable volume of cavity (l)
 76
Cooking method
 Baking stone function, Bottom heat, Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot Air-Eco, Hot air grilling, Roaster function, Top heat
First cavity material
 Oven control electronic
Number of interior lights
 1
Approval certificates
 Australia Standards, CE, Eurasian, G-Mark, Ukraine, VDE
Length electrical supply cord (cm)
 EAN code
 4242006286248

Consumption and connection features

Number of cavities (2010/30/EC)
 1
Energy efficiency class (2010/30/EC)
 A
Energy consumption per cycle conventional (2010/30/EC)
 1.25
Energy consumption gas oven per cycle conventional (2010/30/EC)
 0.83
Energy consumption per cycle forced air convection (2010/30/EC)
 0.83
Energy consumption gas oven per cycle forced air convection (2010/30/EC)
 95.4
Energy efficiency index (2010/30/EC)
 95.4
Connection Rating (W)
 3700
Current (A)
 16
Voltage (V)
 220-240
Frequency (Hz)
 50
Plug type
 no plug
2020-01-08
 Page 1

The outer edge of the door handle extends 72 mm from the furniture cavity.
 Necessary lateral gap between appliance door and furniture panel of min. 5 mm.
 Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.
 When planning a corner solution, pay attention to the 110° door opening angle.
 For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account.
 To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.
 The mains socket needs to be planned outside the built-in niche.
 The LAN port can be found at the back on the upper right side.

Connection

Total connected load 3.7 kW.
 Plan a connection cable.
 Plan a LAN cable.
 Please check the user manual for how to switch off the WiFi module.

Color Variants

BOP251102
Full glass door in Gaggenau Anthracite
Width 60 cm
BOP251112
Full glass door in Gaggenau Metallic
Width 60 cm

Included accessories

1 x enamel baking tray.
 suit. pyrolytic clean.
 1 x glass pan.
 1 x grill shelf.
 1 x pluggable meat probe.

Optional accessories

BA016105
Pull-out system for 60cm ovens
BA056115
Heating element for baking stone and Gastronorm roaster.
BA056133
Baking stone.
GN340230
Gastronorm roaster in cast aluminium.

Product Variants

BOP250102
Oven 200 series
Full glass door in Gaggenau Anthracite
Width 60 cm
right-hinged
Controls at the top