



Color Variants

BX480112
Stainless steel-backed full glass door
Width 76 cm

Included accessories

2 x enamel baking tray.
suit. pyrolytic clean.
1 x rotary spit.
2 x grill shelf.
2 x grill tub with grid.
1 x pluggable meat probe.

Optional accessories

BA018105
Pull-out system
BA058115
Heating element for baking stone and
Gastronorm roaster.
BA058133
Baking stone.
GN340230
Gastronorm roaster in cast aluminium.

Product Variants

BX481112
Double oven 400 series
Stainless steel-backed full glass door
Width 76 cm
left-hinged
Controls centered

BX480112
Double oven 400 series
Stainless steel-backed full glass door
Width 76 cm
right-hinged
Controls centered

Pyrolytic system
17 heating methods, with core
temperature probe, rotisserie spit
and baking stone function
TFT touch display
Electronic temperature control from
30 °C to 300 °C
2 x 110 litres net volume

Heating methods

Hot air.
Eco hot air.
Top + bottom heat.
Top + 1/3 bottom heat.
Top heat.
1/3 top + bottom heat.
Bottom heat.
Hot air + bottom heat.
Hot air + 1/3 bottom heat.
Full surface grill + circulated air.
Full surface grill.
Compact grill.
Baking stone function.
Roaster function.
Dough proving.
Defrosting.
Keeping warm.

Handling

Rotary knob and TFT touch display
operation.
Clear text display in multiple languages.
Information key with use indicators.
Side-opening door opens up to 180°
angle.

Features

Three-point core temperature probe
with automatic shut-off and estimation
of cooking time.
Rotisserie spit (lower oven).
Baking stone socket.
Actual temperature display.
Rapid heating.
Timer functions: cooking time, cooking
time end, timer, stopwatch, long-term
timer.
60 W halogen light on the top.
10 W halogen light on the side.
Enamelled side shelf supports with 5
tray levels, pyrolysis-safe.

Safety

Thermally insulated door with
quadruple glazing.
Child lock.
Safety shut-off.
Cooled housing with temperature
protection.

Cleaning

Pyrolytic system.
Gaggenau enamel.
Heated catalyser to clean the oven air.

Planning notes

Door hinge not reversible.
The door panel surface of the
appliance extends 47 mm from the
furniture cavity.
Consider the overhang when planning
to open drawers next to the appliance.
When planning a corner solution, pay
attention to the 90° door opening
angle.
To achieve the 550 mm installation
depth, the connection cable needs to
follow the slanted edge on the lower
right hand corner of the housing.
The mains socket needs to be planned
outside the built-in niche.

Connection

Characteristics

Color / Material Front
Built-in / Free-standing
Built-in
Integrated Cleaning system
Dimensions of the product (mm)
1428 x 752 x 547
**Dimensions of the packed product
(HxWxD) (mm)**
1600 x 755 x 840
Control Panel Material
Alu
Door Material
Stainless steel behind glass
Net weight (kg)
161.920
Usable volume of cavity (l)
110
Cooking method
Baking stone function, Bottom heat,
Conventional heat, Defrost, Dough
proving setting, Full width grill, Half
width grill, Hot Air, Hot Air-Eco, Hot air
grilling, Roaster function, Top heat,
warming
First cavity material
Enameled
Oven control
electronic
Number of interior lights
2
Approval certificates
Australia Standards, CE, Ukraine, VDE
Length electrical supply cord (cm)
EAN code
4242006284800

Consumption and connection features

Energy efficiency class (2010/30/EC)
A
**Energy consumption per cycle
conventional (2010/30/EC)**
1.53
**Energy consumption gas oven per cycle
conventional (2010/30/EC)**
**Energy consumption per cycle forced
air convection (2010/30/EC)**
0.96
**Energy consumption gas oven per cycle
forced air convection (2010/30/EC)**
**Energy efficiency class (2010/30/EC) -
cavity 2**
A
**Energy consumption per cycle
conventional - cavity 2 (2010/30/EC)**
1.53
**Energy consumption gas oven per cycle
conventional - cavity 2 - NEW (2010/30/
EC)**
**Energy consumption per cycle forced
air convection - cavity 2 (2010/30/EC)**
1.08
**Energy consumption gas oven per
cycle forced air convection - cavity 2
(2010/30/EC)**
Energy efficiency index (2010/30/EC)
95.0
**Energy efficiency index cavity 2
(2010/30/EC)**
106.9
Connection Rating (W)
9200
Current (A)
Voltage (V)
220-240
Frequency (Hz)
50
Plug type
fixed connection, no plug

2019-12-23

Page 1

Total connected load 9.2 kW.

Plan a connection cable.

BX480112
Double oven 400 series
Stainless steel-backed full glass door
Width 76 cm
right-hinged
Controls centered
2019-12-23
Page 2

