

# DFI643

## General description

Turbo Drying™ - Fan assisted moist air extraction  
Style  
Installation type: Fully integrated  
Size: XL, 82 cm  
Number of baskets: 2  
14 place settings  
8 Steel, SCS+  
Upper rack type: Premium - two foldable wine shelves, fixed pin rows and one foldable glass support  
Lower rack type: Premium - foldable pin rows  
Removable cutlery basket for easy unloading

## Construction & Performance

Welded stainless steel container  
Exterior float  
Stand by water protection  
Anti-block drain pump  
8 Steel™ construction  
Hidden heater  
SCS+ (Super Cleaning System+)  
Number of spray arms: 2  
Number of spray zones: 7  
Wide Spray - A spray zone for pots and pans  
Cutlery Power Zone

## Use & Flexibility

Number of place settings: 14 place settings  
Number of baskets: 2  
Upper rack type: Premium - two foldable wine shelves, fixed pin rows and one foldable glass support  
Easy sliding telescope rails with ball bearings for the upper basket  
Lower rack type: Premium - foldable pin rows  
Dense basket wiring in both upper and lower basket  
Removable cutlery basket for easy unloading  
Required inlet water pressure: 0,03-1 MPa

## Interaction & Control

Display type: LCD display  
Customizable programs: Program memory  
Number of programs: 12  
Number of options: 8  
Digital countdown indicator: Time remaining indicator  
Wash end indication: Visual and sound indication washing end

## Programs, options and modes

12 Programs: Eco wash; Hygiene wash; Time program; Plastic wash; Heavy wash; Rinse and hold; Sanitation wash; Upper half wash; Lower half wash; Crystal glass; Quick Pro wash; Self-cleaning  
Delayed start: Variable start delay up to 24 hours  
Super rinse  
Time set  
Green mode  
Speed mode  
Night mode  
Intensive mode  
Extra dry  
High temperature  
Super rinse

## Design & Integration

From front adjustable rear foot  
Velcro strips - easy mounting of door panel  
Min width: 600 mm  
Min height: 820 mm  
Depth (incl. wall spacing): 560 mm  
Height setting: 50 mm  
Kick plate adjustable depth: 30-94 mm

## Safety & Maintenance

Aqua Safe™  
Kid Safe™ - panel  
Rinse-aid indication: Notification in display



## Technical data

Size: 3/4" Can be connected to hot or cold water  
Max. temperature of inflow water: 70 °C  
Noise level: 44 dB(A)re 1 pW  
Reference program: 1  
Total cycle time of reference program (min): 155 min  
Estimated yearly energy consumption: 275 kWh  
Energy consumption reference program: 0,74 kWh  
Energy stars: 3,5  
Water stars: 4,5  
Water consumption: 12,7 l  
Consumption in off mode: 0,5 W  
Consumption in standby mode: 0,5 W  
Plug type: Australia  
Connection rating: 2000 W  
Voltage: 220-240 V  
Number of phases: 1  
Current: 10 amp  
Frequency: 50 Hz  
Required inlet water pressure: 0,03-1 MPa  
Net weight: 44,5 kg  
Yes  
Yes

## Dimensions

Width: 596 mm  
Height: 819 mm  
Depth: 559 mm  
Maximum product height: 869 mm  
Length electrical cord: 1825 mm  
Depth with door open: 1198 mm  
Length inlet hose: 163 cm  
Length outlet hose: 200 cm

## Logistic information

Packaging width: 640 mm  
Packaging height: 890 mm  
Packaging depth: 680 mm  
Gross weight: 47,8 kg  
Product code: 729062  
EAN code: 3838782066986

